

Appt Call

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE: document.record.CPHON1.focus();

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Appt Call

RACEID

- 11 White 1
- 12 Black 1
- 13 Hispanic 1
- 14 Asian/Pacific Islander 1
- 17 American Indian 1
- 18 Don't know 1
- 21 White 2
- 22 Black 2
- 23 Hispanic 2
- 24 Asian/Pacific Islander 2
- 27 American Indian 2
- 28 Don't know 2
- 31 White 3
- 32 Black 3
- 33 Hispanic 3
- 34 Asian/Pacific Islander 3
- 37 American Indian 3
- 38 Don't know 3

VARIABLE: RACEID FORMAT: TRACEID TYPE: N

SKIP CODE:

TESTER ID

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

SEQUENCE

VARIABLE: SEQUENCE FORMAT: integr TYPE: N

SKIP CODE: `this.blur();`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Appt Call

Phone number (000)000-0000

VARIABLE: CPHON1 FORMAT: phone TYPE: A

SKIP CODE:

VARIABLE: CPHON2 FORMAT: phone TYPE: A

SKIP CODE:

Date and time of Call

VARIABLE: HEAD75 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Day of the week

- 1 Monday
- 2 Tuesday
- 3 Wednesday
- 4 Thursday
- 5 Friday
- 6 Saturday
- 7 Sunday

VARIABLE: CDAY FORMAT: DAY TYPE: N

SKIP CODE:

Date (mm/dd/yy)

VARIABLE: CDATE FORMAT: date TYPE: A

SKIP CODE:

Time (_ : _)

VARIABLE: CTIMEH FORMAT: \$HOUR TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Appt Call

AM/PM

1 AM

2 PM

VARIABLE: CTIMEAM FORMAT: AMPM TYPE: N

SKIP CODE:

Call was initiated by

1 Tester

2 Agent

VARIABLE: CINIT FORMAT: CINIT TYPE: N

SKIP CODE:

FOR TESTER INITIATED CALL

VARIABLE: HEAD140 FORMAT: HEADER3 TYPE: H

SKIP CODE:

1 Was the appointment call completed?

1 Yes

0 No

VARIABLE: CCALLC FORMAT: yesno TYPE: N

SKIP CODE: `chk_chk_chk('CINIT','CCALLC','CAPPOINT','1');`

1 Did you make an appointment?

1 Yes

0 No

VARIABLE: CAPPOINT FORMAT: yesno TYPE: N

SKIP CODE: `chk_chk_slct('CCALLC','CAPPOINT','CANOTR','1');`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Appt Call

1 If appointment was NOT made, why not?

- 1 Told no appointment was necessary to visit
- 2 Agent will not make an appointment
- 3 No housing is available
- 4 Test terminated by Test Coordinator
- 5 Other (specify:)

VARIABLE: CANOTR FORMAT: CANOTR TYPE: N

SKIP CODE: canotr()

1 Specify

VARIABLE: CANOTRS FORMAT: \$text32 TYPE: A

SKIP CODE: slct_txt_slct('CANOTR','CANOTRS','CCNOTR','4');

1 If appointment call was NOT completed, why not?

- 1 Left message on voicemail, pager, etc.
- 2 Left message with person
- 3 Told to call back later
- 4 Wrong number
- 5 No answer
- 6 Telephone number no longer in service
- 7 Test terminated by Test Coordinator
- 8 Other (specify:)

VARIABLE: CCNOTR FORMAT: CCNOTR TYPE: N

SKIP CODE: ccnotr()

1 Specify Other

VARIABLE: CCNOTRS FORMAT: \$text32 TYPE: A

SKIP CODE: slct_txt_slct('CCNOTR','CCNOTRS','CCRECV','4');

(If an Appointment Call is not completed, a site visit cannot be conducted.)

VARIABLE: HEAD210 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Appt Call

FOR AGENT INITIATED CALL

VARIABLE: HEAD220 FORMAT: HEADER3 TYPE: H

SKIP CODE:

7 Call was received by

- 1 Tester
 2 Test Coordinator

VARIABLE: CCRECV FORMAT: CCRECV TYPE: N

SKIP CODE: if (document.record.CINIT[0].checked == true) document.record.CCPURP.focus();

7a What was the purpose of the agent's call?

- 1 Confirm appointment time
 2 Cancel appointment and reschedule
 3 Cancelled appointment, but did not reschedule
 4 Other (specify:)

VARIABLE: CCPURP FORMAT: CCPURP TYPE: N

SKIP CODE: if (document.record.CINIT[0].checked == true) document.record.CCPURPS.focus();

7a Specify Other

VARIABLE: CCPURPS FORMAT: \$text32 TYPE: A

SKIP CODE: slct_txt_slct('CCPURP','CCPURPS','CAPTDD','4');

When is your appointment?

VARIABLE: HEAD260 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Appt Call

2 Day of the week

- 1 Monday
- 2 Tuesday
- 3 Wednesday
- 4 Thursday
- 5 Friday
- 6 Saturday
- 7 Sunday

VARIABLE: CAPTDD FORMAT: DAY TYPE: N

SKIP CODE: captdd()

2 Date (mm/dd/yy)

VARIABLE: CAPTD FORMAT: date TYPE: A

SKIP CODE: //slct_txt_txt2('CAPTDD','CAPTD','CAPTTH','0');

2 Time (_:_)

VARIABLE: CAPTTH FORMAT: \$HOUR TYPE: A

SKIP CODE: //txt_txt_slct('CAPTD','CAPTTH','CAPTTAM','0');

2 AM/PM

- 1 AM
- 2 PM

VARIABLE: CAPTTAM FORMAT: AMPM TYPE: N

SKIP CODE: //slct_slct_txt('CAPTDD','CAPTTAM','CANAME','0');

3 Name of the person you have appointment with

VARIABLE: CANAME FORMAT: \$text32 TYPE: A

SKIP CODE: //slct_txt_txt2('CAPTDD','CANAME','CLOCTN','0');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Appt Call

4 Location to meet

VARIABLE: CLOCTN FORMAT: \$text64 TYPE: A
SKIP CODE: //slct_txt_txt2('CAPTDD','CLOCTN','CNSPOKE','0');

5 Name of person you spoke with during this contact

VARIABLE: CNSPOKE FORMAT: \$text32 TYPE: A
SKIP CODE: //slct_txt_txt2('CAPTDD','CNSPOKE','CCOMNT','0');

6 Additional Information

VARIABLE: CCOMNT FORMAT: \$text240 TYPE: A
SKIP CODE: //txt_txt_chk2('CNSPOKE','CCOMNT','COMP','0');

6 This form is complete

1 Yes
 0 No

VARIABLE: COMP FORMAT: YESNO TYPE: N
SKIP CODE:

6 Test Released

1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A
SKIP CODE: document.record.COMP[0].focus();

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE: `document.record.RUADD.focus();`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

RACEID

- 11 White 1
- 12 Black 1
- 13 Hispanic 1
- 14 Asian/Pacific Islander 1
- 17 American Indian 1
- 18 Don't know 1
- 21 White 2
- 22 Black 2
- 23 Hispanic 2
- 24 Asian/Pacific Islander 2
- 27 American Indian 2
- 28 Don't know 2
- 31 White 3
- 32 Black 3
- 33 Hispanic 3
- 34 Asian/Pacific Islander 3
- 37 American Indian 3
- 38 Don't know 3

VARIABLE: RACEID FORMAT: TRACEID TYPE: N

SKIP CODE:

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

TESTER ID

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

SEQUENCE

VARIABLE: SEQUAU FORMAT: INTEGR TYPE: N

SKIP CODE: this.blur();

1 Address of Available Unit

VARIABLE: RUHEAD1 FORMAT: HEADER3 TYPE: H

SKIP CODE:

1 Number and Street

VARIABLE: RUADD FORMAT: \$text64 TYPE: A

SKIP CODE:

1 street type

- 1 Avenue
- 2 Blvd
- 3 Circle
- 4 Court
- 5 Drive
- 6 Highway
- 7 Parkway
- 8 Lane
- 9 Street
- 10 Road
- 11 Place
- 12 Route
- 13 Terrace
- 14 Path

VARIABLE: RUSITETP FORMAT: STRTYP TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

1 unit number

VARIABLE: RUNO FORMAT: \$text8 TYPE: A
SKIP CODE:

1 city

VARIABLE: RUCITY FORMAT: \$text32 TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

1 state

- AK AK - Alaska
- AL AL - Alabama
- AR AR - Arkansas
- AZ AZ - Arizona
- CA CA - California
- CO CO - Colorado
- CT CT - Connecticut
- DC DC - District of Columbia
- DE DE - Delaware
- FL FL - Florida
- GA GA - Georgia
- HI HI - Hawaii
- IA IA - Iowa
- ID ID - Idaho
- IL IL - Illinois
- IN IN - Indiana
- KS KS - Kansas
- KY KY - Kentucky
- LA LA - Louisiana
- MA MA - Massachusetts
- MD MD - Maryland
- ME ME - Maine
- MI MI - Michigan
- MN MN - Minnesota
- MO MO - Missouri
- MS MS - Mississippi
- MT MT - Montana
- NC NC - North Carolina
- ND ND - North Dakota
- NE NE - Nebraska
- NH NH - New Hampshire
- NJ NJ - New Jersey
- NM NM - New Mexico
- NV NV - Nevada
- NY NY - New York
- OH OH - Ohio
- OK OK - Oklahoma

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

- OR OR - Oregon
- PA PA - Pennsylvania
- RI RI - Rhode Island
- SC SC - South Carolina
- SD SD - South Dakota
- TN TN - Tennessee
- TX TX - Texas
- UT UT - Utah
- VA VA - Virginia
- VT VT - Vermont
- WA WA - Washington
- WI WI - Wisconsin
- WV WV - West Virginia
- WY WY - Wyoming

VARIABLE: RUST FORMAT: \$STATE TYPE: A
SKIP CODE:

1 ZIP 00000

VARIABLE: RUZIP FORMAT: \$zip TYPE: A
SKIP CODE:

1a Type of Building

- 1 Apartment building - 4 or fewer units
- 2 Apartment building - 5 or more units
- 3 Single-family home
- 4 Mobile home

VARIABLE: RUBTYP FORMAT: RUBTYP TYPE: A
SKIP CODE:

2 Did you inspect this unit?

- 1 Yes
- 0 No

VARIABLE: RUINSP FORMAT: YESNO TYPE: N
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

3 Is this the advertised unit?

1 Yes

0 No

VARIABLE: RUINAD FORMAT: YESNO TYPE: N

SKIP CODE:

4 Were you shown a model similar to the available unit?

1 Yes

0 No

VARIABLE: RUMODL FORMAT: yesno TYPE: N

SKIP CODE:

5 Date available (mm/dd/yy)

VARIABLE: RUAVLBL FORMAT: date TYPE: A

SKIP CODE:

6 How much is the rent? (\$__ /month)

VARIABLE: RURENT FORMAT: n5 TYPE: N

SKIP CODE:

7 Number of bedrooms

VARIABLE: RUBED FORMAT: integr TYPE: N

SKIP CODE:

8 Number of bathrooms

VARIABLE: RUBATH FORMAT: integr TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

9 How many floors in building?

VARIABLE: RUFLRBL FORMAT: FLOOR TYPE: N
SKIP CODE:

10 Unit is on what floor?

VARIABLE: RUFLOOR FORMAT: integr TYPE: N
SKIP CODE:

11 Length of Lease (check all that apply)

VARIABLE: RUHEAD2 FORMAT: HEADER3 TYPE: H
SKIP CODE:

11 Month-to-month

- 1 Yes
 0 No

VARIABLE: RULMM FORMAT: YESNO TYPE: N
SKIP CODE:

11 Three Month

- 1 Yes
 0 No

VARIABLE: RUL3M FORMAT: YESNO TYPE: N
SKIP CODE:

11 Six month

- 1 Yes
 0 No

VARIABLE: RUL6M FORMAT: YESNO TYPE: N
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

11 One year

- 1 Yes
 0 No

VARIABLE: RUL1Y FORMAT: YESNO TYPE: N
SKIP CODE:

11 Two year

- 1 Yes
 0 No

VARIABLE: RUL2Y FORMAT: yesno TYPE: N
SKIP CODE:

11 Other

- 1 Yes
 0 No

VARIABLE: RULOL FORMAT: YESNO TYPE: N
SKIP CODE:

11 Specify

VARIABLE: RULOLS FORMAT: \$text64 TYPE: A
SKIP CODE: `chk_txt_slct('RULOL','RULOLS','RUINTER','1');`

12 How do you rate the physical condition of the unit's INTERIOR?

- 1 Clean and in excellent repair, move in condition
 2 Some cleaning and minor maintenance needed, adequa
 3 Very dirty and in need of substantial maintenance,
 4 Not applicable (did not view or unit was a model)

VARIABLE: RUINTER FORMAT: CONDITN TYPE: N
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

13 How do you rate the physical condition of the unit's EXTERIOR?

- 1 Clean and in excellent repair, move in condition
- 2 Some cleaning and minor maintenance needed, adequate
- 3 Very dirty and in need of substantial maintenance,
- 4 Not applicable (did not view or unit was a model)

VARIABLE: RUEXTR FORMAT: CONDITN TYPE: N

SKIP CODE:

14 What utilities are included in rent? (check all that apply)

VARIABLE: RUHEAD3 FORMAT: HEADER3 TYPE: H

SKIP CODE:

14 Agent did not know

- 1 Yes
- 0 No

VARIABLE: RUAGDKU FORMAT: yesno TYPE: N

SKIP CODE:

14 Electric

- 1 Yes
- 0 No

VARIABLE: RUELCIN FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('RUAGDKU','RUELCIN','RUGASIN','0');

14 Gas

- 1 Yes
- 0 No

VARIABLE: RUGASIN FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('RUAGDKU','RUGASIN','RUH2OIN','0');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

14 Water

1 Yes

0 No

VARIABLE: RUH2OIN FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('RUAGDKU','RUH2OIN','RUPRTU','0');

14 Partial utilities (i.e., extra for seasonal heating/cooling)

1 Yes

0 No

VARIABLE: RUPRTU FORMAT: yesno TYPE: N

SKIP CODE: chk_chk_chk('RUAGDKU','RUPRTU','RUOTRU','0');

14 Other utilities

1 Yes

0 No

VARIABLE: RUOTRU FORMAT: yesno TYPE: N

SKIP CODE: chk_chk_txt('RUAGDKU','RUOTRU','RUOTRUS','0');

14 Specify

VARIABLE: RUOTRUS FORMAT: \$text64 TYPE: A

SKIP CODE: chk_txt_chk('RUOTRU','RUOTRUS','RUPARK','1');

15 What amenities were you told about (check all that apply)

VARIABLE: RUHEAD4 FORMAT: HEADER3 TYPE: H

SKIP CODE:

15 Parking

1 Yes

0 No

VARIABLE: RUPARK FORMAT: yesno TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

15 Cable TV

1 Yes

0 No

VARIABLE: RUCABLE FORMAT: yesno TYPE: N

SKIP CODE:

15 Washer & Dryer/ Laundry Facility

1 Yes

0 No

VARIABLE: RUWD FORMAT: yesno TYPE: N

SKIP CODE:

15 Pool/Health Club

1 Yes

0 No

VARIABLE: RUPOOL FORMAT: yesno TYPE: N

SKIP CODE:

15 Other amenities

1 Yes

0 No

VARIABLE: RUOTRA FORMAT: yesno TYPE: N

SKIP CODE:

15 Specify

VARIABLE: RUOTRAS FORMAT: \$text64 TYPE: A

SKIP CODE:

16 Fees: Specify any fees that you were told would be required AT THE TIME OF APPLICATION

VARIABLE: RYHEAD5 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

16

VARIABLE: TABHEAD0 FORMAT: THEADER TYPE: H
SKIP CODE:

Name of Fee

VARIABLE: TABHEAD1 FORMAT: THEADER TYPE: H
SKIP CODE:

Amount of Fee

VARIABLE: TABHEAD2 FORMAT: THEADER TYPE: H
SKIP CODE:

16 **First fee**

VARIABLE: RUFEEEN1 FORMAT: \$text64 TYPE: A
SKIP CODE:

16 **Amount of first fee**

VARIABLE: RUFEEA1 FORMAT: N6 TYPE: N
SKIP CODE:

16 **Second fee**

VARIABLE: RUFEEEN2 FORMAT: \$text64 TYPE: A
SKIP CODE:

16 **Amount of second fee**

VARIABLE: RUFEEA2 FORMAT: N6 TYPE: N
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

16 Third fee

VARIABLE: RUFEEEN3 FORMAT: \$text64 TYPE: A
SKIP CODE:

16 Amount of third fee

VARIABLE: RUFEEA3 FORMAT: N6 TYPE: N
SKIP CODE:

16 Fourth fee

VARIABLE: RUFEEEN4 FORMAT: \$text64 TYPE: A
SKIP CODE:

16 Amount of fourth fee

VARIABLE: RUFEEA4 FORMAT: N6 TYPE: N
SKIP CODE:

16 Enter the TOTAL AMOUNT (in dollars) of the fees you were told would be required at the time of application.

VARIABLE: RUTOTFEE FORMAT: N6 TYPE: N
SKIP CODE: addFees();

17 Security Deposit

VARIABLE: RUHEAD6 FORMAT: HEADER3 TYPE: H
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

17 Is a security deposit required?

- 1 Yes
 2 No
 3 Agent did not know

VARIABLE: RUDEPST FORMAT: YNDK TYPE: N

SKIP CODE:

17a If yes, how much is it?

VARIABLE: RUDEPST5 FORMAT: n5 TYPE: N

SKIP CODE: chk_txt_chk2('RUDEPST','RUDEPST5','RUWAIT','0');

18 Waiting List

VARIABLE: RUHEAD7 FORMAT: HEADER3 TYPE: H

SKIP CODE:

18 Were you told there was a waiting list for this unit?

- 1 Yes
 0 No

VARIABLE: RUWAIT FORMAT: yesno TYPE: N

SKIP CODE:

18a If yes, how many people were you told were on the list?

VARIABLE: RUWAITN FORMAT: N4 TYPE: N

SKIP CODE: chk_txt_chk('RUWAIT','RUWAITN','RUWAITL','1');

18b If yes, did the agent offer to place your name on the list?

- 1 Yes
 0 No

VARIABLE: RUWAITL FORMAT: yesno TYPE: N

SKIP CODE: chk_chk_chk('RUWAIT','RUWAITL','RUSPCL','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

19 Rent Specials

VARIABLE: RUHEAD8 FORMAT: HEADER3 TYPE: H

SKIP CODE:

19 Were you told of any rent special or other incentives that you would receive if you were to rent this particular unit?

1 Yes

0 No

VARIABLE: RUSPCL FORMAT: yesno TYPE: N

SKIP CODE:

19a If yes, please describe

VARIABLE: RUSPCLS FORMAT: \$text240 TYPE: A

SKIP CODE: `chk_txt_slct('RUSPCL','RUSPCLS','RUCNOIS','1');`

20 Did the Agent make any of the following comments about the surrounding neighborhood?

VARIABLE: RUHEAD9 FORMAT: HEADER3 TYPE: H

SKIP CODE:

20a Noise

1 Quiet

2 Noisy

3 No comment

VARIABLE: RUCNOIS FORMAT: noise TYPE: N

SKIP CODE:

20b Safety

1 Safe/low crime

2 Dangerous/high crime

3 No comment

VARIABLE: RUCSAFE FORMAT: safety TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

20c Schools

- 1 Good
- 2 Poor
- 3 No comment

VARIABLE: RUCSCHL FORMAT: schools TYPE: N

SKIP CODE:

20d Maintenance/ Services

- 1 Good services/amenities
- 2 Poor/unreliable services
- 3 No comment

VARIABLE: RUCSRVE FORMAT: pubserv TYPE: N

SKIP CODE:

20e Race or ethnicity

- 1 Yes
- 0 No

VARIABLE: RUCRACE FORMAT: YESNO TYPE: N

SKIP CODE:

20e If yes, please record what the agent said

VARIABLE: RUCRACTX FORMAT: \$text500 TYPE: A

SKIP CODE: `chk_txt_chk('RUCRACE','RUCRACTX','COMP','1');`

This form is complete

- 1 Yes
- 0 No

VARIABLE: COMP FORMAT: YESNO TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Avail Unit

Test Released

1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A

SKIP CODE: document.record.COMP[0].focus();

Delete this record (for TC use only)

1 Yes

0 No

VARIABLE: DELREC FORMAT: YESNO TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

FAF

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

0 CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TEST COORDINATOR SECTION

VARIABLE: header2 FORMAT: HEADER3 TYPE: H

SKIP CODE:**0 TC ID #**

VARIABLE: TCID FORMAT: TESTERID TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Week

- 01 1 (05/03/01 to 05/09/01)
- 02 2 (05/10/01 to 05/16/01)
- 03 3 (05/17/01 to 05/23/01)
- 04 4 (05/24/01 to 05/30/01)
- 05 5 (05/31/01 to 06/06/01)
- 06 6 (06/07/01 to 06/13/01)
- 07 7 (06/14/01 to 06/20/01)
- 08 8 (06/21/01 to 06/27/01)
- 09 9 (06/28/01 to 07/04/01)
- 10 10 (07/05/01 to 07/11/01)
- 11 11 (07/12/01 to 07/18/01)
- 12 12 (07-19-01 to 07-25-01)
- 13 13 (07-26-01 to 08-01-01)
- 14 14 (08-02-01 to 08-08-01)
- 15 15 (08-09-01 to 08-15-01)
- 16 16 (08-16-01 to 08-22-01)
- 17 17 (08-23-01 to 08-29-01)
- 18 18 (08-30-01 to 09-05-01)
- 19 19 (09-06-01 to 09-12-01)
- 20 20 (09-13-01 to 09-19-01)
- 21 21 (09-20-01 to 09-26-01)
- 22 22 (09-27-01 to 10-03-01)
- 23 23 (10-04-01 to 10-10-01)
- 24 24 (10-11-01 to 10-17-01)
- 25 25 (10-18-01 to 10-24-01)
- 26 26 (10-25-01 to 10-31-01)
- 27 27 (11-01-01 to 11-07-01)
- 28 28 (11-08-01 to 11-14-01)
- 29 29 (11-15-01 to 11-21-01)
- 30 30 (11-22-01 to 11-28-01)
- 31 31 (11-29-01 to 12-05-01)
- 32 32 (12-06-01 to 12-12-01)
- 33 33 (12-13-01 to 12-19-01)
- 34 34 (12-20-01 to 12-26-01)
- 35 35 (12-27-01 to 01-02-02)
- 36 36 (01-03-02 to 01-09-02)
- 37 37 (01-10-02 to 01-16-02)

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

- 38 38 (01-17-02 to 01-23-02)
- 39 39 (01-24-02 to 01-30-02)
- 40 40 (01-31-02 to 02-06-02)
- 41 41 (02-07-02 to 02-13-02)
- 42 42 (02-14-02 to 02-20-02)
- 43 43 (02-21-02 to 02-27-02)
- 44 44 (02-28-02 to 03-06-02)
- 45 45 (03-07-02 to 03-13-02)
- 46 46 (03-14-02 to 03-20-02)
- 47 47 (03-21-02 to 03-27-02)
- 48 48 (03-28-02 to 04-03-02)
- 49 49 (04-04-02 to 04-10-02)
- 50 50 (04-11-02 to 04-17-02)
- 51 51 (04-18-02 to 04-24-02)

VARIABLE: WEEK FORMAT: WEEKNUM TYPE: N
SKIP CODE:

1 Test Was Completed

- 1 Yes
- 0 No

VARIABLE: FCOMPLT FORMAT: YESNO TYPE: N
SKIP CODE:

2 Reason why test was not completed

- 0 Ad was ineligible, test not assigned
- 9 Not Applicable
- 38 Ad was eligible, but test not completed

VARIABLE: FELYNO FORMAT: ELIGTC TYPE: N
SKIP CODE: `chk_slct_txt('FCOMPLT','FELYNO','FELYNOS','1')`

2 Ad was eligible, but test not completed (use only as directed by Regional Coordinator) Specify

VARIABLE: FELYNOS FORMAT: \$TEXT128 TYPE: A
SKIP CODE: `slct_txt_txt('FELYNO','FELYNOS','FINEL','3');`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

3 Reason ad was ineligible

- 41 Outside of target area
- 42 Seasonal/temporary/vacation/short-term
- 46 Agency no longer in business
- 47 No address and incorrect phone number in ad
- 49 Agency already selected for same race tenure test
- 51 For Sale By Owner
- 52 Exceeds price range
- 53 Multi-unit structure for sale
- 54 Housing for Older Persons
- 56 Unimproved lot, to be constructed
- 57 Mobile Home Sale Through Dealership
- 61 Share situation
- 62 Apartment Locator Service
- 64 Sublet
- 66 Public/Subsidized housing development
- 67 No testers available to test housing provider
- 99 Other (Specify:)

VARIABLE: FINEL FORMAT: PINELR TYPE: N

SKIP CODE: slct_slct_txt2('FELYNO','FINEL','FINELS','1');

3 Other [Specify]

VARIABLE: FINELS FORMAT: \$TEXT128 TYPE: A

SKIP CODE: slct_txt_txt('FINEL','FINELS','FNOTETC','17');

4 Notes

VARIABLE: FNOTETC FORMAT: \$TEXT128 TYPE: A

SKIP CODE:

REGIONAL COORDINATOR SECTION

VARIABLE: header10 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

FAF

0 RC ID

VARIABLE: RCID FORMAT: TESTERID TYPE: A

SKIP CODE:

5 Did test pass quality review?

1 Yes

0 No

VARIABLE: FPASS FORMAT: YESNO TYPE: N

SKIP CODE:

6 Reason that test did not pass quality review

31 Terminated by local testing organization (specify)

32 Protocol violation (specify)

33 Test fabricated (whole or part)

34 Detection

35 Forms missing; test file incomplete

36 Key data items missing

37 Other (specify)

VARIABLE: FNPASS FORMAT: NPASS TYPE: N

SKIP CODE: `chk_slct_txt('FPASS','FNPASS','FNP31S','1');`

6 Terminated by Local Testing Organization (Specify)

VARIABLE: FNP31S FORMAT: \$TEXT128 TYPE: A

SKIP CODE: `txt_txt_txt('FNPASS','FNP31S','FNP32S','31');`

6 Protocol Violation (Specify)

VARIABLE: FNP32S FORMAT: \$TEXT128 TYPE: A

SKIP CODE: `txt_txt_txt('FNPASS','FNP32S','FNP37S','32');`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

FAF

6 Other (Specify)

VARIABLE: FNP37S FORMAT: \$TEXT128 TYPE: A

SKIP CODE: txt_txt_txt('FNPASS','FNP37S','FNOTERC','37');

7 Notes

VARIABLE: FNOTERC FORMAT: \$TEXT128 TYPE: A

SKIP CODE:

1 Yes

2 No

VARIABLE: RELEASE FORMAT: \$YESNO TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

FAF TC

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

0 CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TEST COORDINATOR SECTION

VARIABLE: header2 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

FAF TC

Week

- 01 1 (05/03/01 to 05/09/01)
- 02 2 (05/10/01 to 05/16/01)
- 03 3 (05/17/01 to 05/23/01)
- 04 4 (05/24/01 to 05/30/01)
- 05 5 (05/31/01 to 06/06/01)
- 06 6 (06/07/01 to 06/13/01)
- 07 7 (06/14/01 to 06/20/01)
- 08 8 (06/21/01 to 06/27/01)
- 09 9 (06/28/01 to 07/04/01)
- 10 10 (07/05/01 to 07/11/01)
- 11 11 (07/12/01 to 07/18/01)
- 12 12 (07-19-01 to 07-25-01)
- 13 13 (07-26-01 to 08-01-01)
- 14 14 (08-02-01 to 08-08-01)
- 15 15 (08-09-01 to 08-15-01)
- 16 16 (08-16-01 to 08-22-01)
- 17 17 (08-23-01 to 08-29-01)
- 18 18 (08-30-01 to 09-05-01)
- 19 19 (09-06-01 to 09-12-01)
- 20 20 (09-13-01 to 09-19-01)
- 21 21 (09-20-01 to 09-26-01)
- 22 22 (09-27-01 to 10-03-01)
- 23 23 (10-04-01 to 10-10-01)
- 24 24 (10-11-01 to 10-17-01)
- 25 25 (10-18-01 to 10-24-01)
- 26 26 (10-25-01 to 10-31-01)
- 27 27 (11-01-01 to 11-07-01)
- 28 28 (11-08-01 to 11-14-01)
- 29 29 (11-15-01 to 11-21-01)
- 30 30 (11-22-01 to 11-28-01)
- 31 31 (11-29-01 to 12-05-01)
- 32 32 (12-06-01 to 12-12-01)
- 33 33 (12-13-01 to 12-19-01)
- 34 34 (12-20-01 to 12-26-01)
- 35 35 (12-27-01 to 01-02-02)
- 36 36 (01-03-02 to 01-09-02)
- 37 37 (01-10-02 to 01-16-02)

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)}. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

FAF TC

- 38 38 (01-17-02 to 01-23-02)
- 39 39 (01-24-02 to 01-30-02)
- 40 40 (01-31-02 to 02-06-02)
- 41 41 (02-07-02 to 02-13-02)
- 42 42 (02-14-02 to 02-20-02)
- 43 43 (02-21-02 to 02-27-02)
- 44 44 (02-28-02 to 03-06-02)
- 45 45 (03-07-02 to 03-13-02)
- 46 46 (03-14-02 to 03-20-02)
- 47 47 (03-21-02 to 03-27-02)
- 48 48 (03-28-02 to 04-03-02)
- 49 49 (04-04-02 to 04-10-02)
- 50 50 (04-11-02 to 04-17-02)
- 51 51 (04-18-02 to 04-24-02)

VARIABLE: WEEK FORMAT: WEEKNUM TYPE: N
SKIP CODE:

0 TC ID

VARIABLE: TCID FORMAT: TESTERID TYPE: A
SKIP CODE:

1 Test Was Completed

- 1 Yes
- 0 No

VARIABLE: FCOMPLT FORMAT: YESNO TYPE: N
SKIP CODE:

2 Reason why test was not completed

- 0 Ad was ineligible, test not assigned
- 9 Not Applicable
- 38 Ad was eligible, but test not completed

VARIABLE: FELYNO FORMAT: ELIGTC TYPE: N
SKIP CODE: `chk_slct_txt('FCOMPLT','FELYNO','FELYNOS','1')`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

FAF TC

2 Ad was eligible, but test not completed (use only as directed by Regional Coordinator) Specify

VARIABLE: FELYNOS FORMAT: \$TEXT128 TYPE: A

SKIP CODE: slct_txt_txt('FELYNO','FELYNOS','FINEL','3');

3 Reason ad was ineligible

- 41 Outside of target area
- 42 Seasonal/temporary/vacation/short-term
- 46 Agency no longer in business
- 47 No address and incorrect phone number in ad
- 49 Agency already selected for same race tenure test
- 51 For Sale By Owner
- 52 Exceeds price range
- 53 Multi-unit structure for sale
- 54 Housing for Older Persons
- 56 Unimproved lot, to be constructed
- 57 Mobile Home Sale Through Dealership
- 61 Share situation
- 62 Apartment Locator Service
- 64 Sublet
- 66 Public/Subsidized housing development
- 67 No testers available to test housing provider
- 99 Other (Specify:)

VARIABLE: FINEL FORMAT: PINELR TYPE: N

SKIP CODE: slct_slct_txt2('FELYNO','FINEL','FINELS','1');

3 Other [Specify]

VARIABLE: FINELS FORMAT: \$TEXT128 TYPE: A

SKIP CODE: slct_txt_txt('FINEL','FINELS','FNOTETC','17');

4 Notes

VARIABLE: FNOTETC FORMAT: \$TEXT128 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

FAF TC

1 Yes

2 No

VARIABLE: RELEASE

FORMAT: \$YESNO

TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Follow Up

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE: `document.record.SEQFUC.focus();`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Follow Up

RACEID

- 11 White 1
- 12 Black 1
- 13 Hispanic 1
- 14 Asian/Pacific Islander 1
- 17 American Indian 1
- 18 Don't know 1
- 21 White 2
- 22 Black 2
- 23 Hispanic 2
- 24 Asian/Pacific Islander 2
- 27 American Indian 2
- 28 Don't know 2
- 31 White 3
- 32 Black 3
- 33 Hispanic 3
- 34 Asian/Pacific Islander 3
- 37 American Indian 3
- 38 Don't know 3

VARIABLE: RACEID FORMAT: TRACEID TYPE: N

SKIP CODE:

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

TESTER ID

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Follow Up

SEQUENCE

VARIABLE: SEQFUC FORMAT: INTEGR TYPE: N

SKIP CODE: this.blur();

1 Was there any follow up contact?

1 Yes

0 No

VARIABLE: LYNCONT FORMAT: YESNO TYPE: N

SKIP CODE:

Date and Time of contact

VARIABLE: LHEAD1 FORMAT: HEADER3 TYPE: H

SKIP CODE:

2 Day of the week

1 Monday

2 Tuesday

3 Wednesday

4 Thursday

5 Friday

6 Saturday

7 Sunday

VARIABLE: LDAY FORMAT: DAY TYPE: N

SKIP CODE:

2 Date (mm/dd/yy)

VARIABLE: LDATE FORMAT: date TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Follow Up

2 Time (_ _ : _ _)

VARIABLE: LTIMEH FORMAT: \$HOUR TYPE: A

SKIP CODE:

2 AM/PM

1 AM

2 PM

VARIABLE: LTIMEAM FORMAT: ampm TYPE: N

SKIP CODE:

3 Type of contact

1 Telephone call to tester at home

2 Telephone message left at tester's home

3 Voice mail message retrieved by Test Coordinator

4 Postal mail

5 Email

6 Other (specify:)

VARIABLE: LCONTYPE FORMAT: LCONTYPE TYPE: N

SKIP CODE:

3 Specify

VARIABLE: LCONTYPS FORMAT: \$text32 TYPE: A

SKIP CODE: slct_txt_txt('LCONTYPE','LCONTYPS','LCONNAME','6');

4 Name of person making contact

VARIABLE: LCONNAME FORMAT: \$text64 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Follow Up

5 Name of agency making contact (if given)

VARIABLE: LAGENCY FORMAT: \$text64 TYPE: A

SKIP CODE:

What was the stated purpose of the contact? (Check all that apply)

VARIABLE: LHEAD2 FORMAT: HEADER3 TYPE: H

SKIP CODE:

6 Agent wanted to see if tester is still interested in purchase/rental

1 Yes

0 No

VARIABLE: LPRPSTL FORMAT: YESNO TYPE: N

SKIP CODE:

6 Agent wanted to recommend a lender to the tester

1 Yes

0 No

VARIABLE: LPRPRECL FORMAT: YESNO TYPE: N

SKIP CODE:

6 Agent wanted to let tester know about more housing

1 Yes

0 No

VARIABLE: LPRPMORE FORMAT: YESNO TYPE: N

SKIP CODE:

6 Agent wanted to get more information from tester

1 Yes

0 No

VARIABLE: LPRPINFO FORMAT: YESNO TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Follow Up

6 Other (specify)

1 Yes

0 No

VARIABLE: LRPOTHR FORMAT: YESNO TYPE: N

SKIP CODE:

6 Specify

VARIABLE: LRPPOS FORMAT: \$text32 TYPE: A

SKIP CODE: `chk_txt_chk('LRPOTHR','LRPPOS','LRPTNK','1');`

6 Agent wanted to thank tester

1 Yes

0 No

VARIABLE: LRPTNK FORMAT: YESNO TYPE: N

SKIP CODE:

7 Describe any materials received

VARIABLE: LMATD FORMAT: \$text240 TYPE: A

SKIP CODE:

This form is complete

1 Yes

0 No

VARIABLE: COMP FORMAT: YESNO TYPE: N

SKIP CODE:

Delete this record (for TC use only)

1 Yes

0 No

VARIABLE: DELREC FORMAT: YESNO TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Follow Up

Test Released

1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A

SKIP CODE: `document.record.COMP[0].focus();`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Hire Track

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

Name

VARIABLE: TNAME FORMAT: \$TEXT64 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Hire Track

Tester ID#

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

Sex

0 Female

1 Male

VARIABLE: TSEX FORMAT: SEX TYPE: N

SKIP CODE:

Date of Birth (mm/dd/yy)

VARIABLE: TDOB FORMAT: DATE TYPE: A

SKIP CODE:

Race

1 White

2 Black/African-American

3 American Indian/Native American

4 Asian/Pacific Islander

5 Other (Specify)

VARIABLE: APRACE FORMAT: APRACE TYPE: N

SKIP CODE:

National Origin

1 Non-Hispanic

2 Hispanic

VARIABLE: TNATORIG FORMAT: TNATORIG TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Hire Track

Possible Matches (enter tester ID numbers)

VARIABLE: TMATCH FORMAT: \$text64 TYPE: A

SKIP CODE:

Selected? Y/N

1 Yes

0 No

VARIABLE: THIED FORMAT: YESNO TYPE: N

SKIP CODE:

Is this Tester Active?

1 Yes

0 No

VARIABLE: TACTIVE FORMAT: YESNO TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Neighborhood

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE: `document.record.SNHBRNAM.focus();`

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Neighborhood

TESTER ID

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

RACEID

- 11 White 1
- 12 Black 1
- 13 Hispanic 1
- 14 Asian/Pacific Islander 1
- 17 American Indian 1
- 18 Don't know 1
- 21 White 2
- 22 Black 2
- 23 Hispanic 2
- 24 Asian/Pacific Islander 2
- 27 American Indian 2
- 28 Don't know 2
- 31 White 3
- 32 Black 3
- 33 Hispanic 3
- 34 Asian/Pacific Islander 3
- 37 American Indian 3
- 38 Don't know 3

VARIABLE: RACEID FORMAT: TRACEID TYPE: N

SKIP CODE:

SEQUENCE

VARIABLE: SEQSNI FORMAT: integr TYPE: N

SKIP CODE: this.blur();

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Neighborhood

1 Name of area

VARIABLE: SNHBRNAM FORMAT: \$text64 TYPE: A

SKIP CODE:

2 This area is a:

- 1 County
- 2 Town or City
- 3 School District
- 4 Neighborhood
- 5 Don't know

VARIABLE: SNHBR TYP FORMAT: NHBRTYP TYPE: N

SKIP CODE:

3 Did the agent make any of the following comments about the surrounding neighborhood?

VARIABLE: SNBRHD1 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Did the agent make any of the following comments about the surrounding neighborhood?

VARIABLE: SNHEAD1 FORMAT: HEADER3 TYPE: H

SKIP CODE:

3a Noise

- 1 Quiet
- 2 Noisy
- 3 No comment

VARIABLE: SNBRNOIS FORMAT: NOISE TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Neighborhood

3b Safety

- 1 Safe/low crime
- 2 Dangerous/high crime
- 3 No comment

VARIABLE: SNBRSAFE FORMAT: SAFETY TYPE: N

SKIP CODE:

3c Schools

- 1 Good
- 2 Poor
- 3 No comment

VARIABLE: SNBRSCHL FORMAT: SCHOOLS TYPE: N

SKIP CODE:

3d Investment

- 1 Rising values/good investment
- 2 Flat values/ not much appreciation
- 3 Declining values/depreciation
- 4 No comment

VARIABLE: SNBRINVS FORMAT: INVEST TYPE: N

SKIP CODE:

3e Public Services

- 1 Good services/amenities
- 2 Poor/unreliable services
- 3 No comment

VARIABLE: SNBRPUBS FORMAT: PUBSERV TYPE: N

SKIP CODE:

3f Race or Ethnicity

- 1 Yes
- 0 No

VARIABLE: SAGNHC FORMAT: YESNO TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Neighborhood

3f If yes, please record what the agent said:

VARIABLE: SAGNHTX FORMAT: \$text500 TYPE: A

SKIP CODE: `chk_txt_chk('SAGNHC','SAGNHTX','COMP','1');`

This form is complete

1 Yes

0 No

VARIABLE: COMP FORMAT: YESNO TYPE: N

SKIP CODE:

Delete this record (for TC use only)

1 Yes

0 No

VARIABLE: DELREC FORMAT: YESNO TYPE: N

SKIP CODE:

Test Released

1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A

SKIP CODE: `document.record.COMP[0].focus();`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

Transaction Type

R Rental

S Sales

VARIABLE: TRANTYPE FORMAT: \$TAFTYP TYPE: A

SKIP CODE:

Site

AG Augusta, GA

AH Anaheim, CA

BA Baltimore, MD

BU Buffalo, NY

CH Chicago, IL

CO Columbus, GA

DC Washington, DC

HN Honolulu, HI

HU Huntsville, AL

MB Mobile, AL

MI Miami, FL

MY Montgomery, AL

NS Nassau-Suffolk County, NY

NY New York, NY

OK Oakland, CA

PH Philadelphia, PA

PT Pittsburgh, PA

RO Rochester, NY

RV Riverside, CA

SD San Diego, CA

SF San Francisco, CA

SJ San Jose, CA

SV Savannah, GA

XX UI Internal Test Site

ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Housing Provider Information

VARIABLE: header2 FORMAT: HEADER3 TYPE: H

SKIP CODE:

1 Name (of Agent/Company/Complex)

VARIABLE: PPNAME FORMAT: \$TEXT64 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

Week

- 01 1 (05/03/01 to 05/09/01)
- 02 2 (05/10/01 to 05/16/01)
- 03 3 (05/17/01 to 05/23/01)
- 04 4 (05/24/01 to 05/30/01)
- 05 5 (05/31/01 to 06/06/01)
- 06 6 (06/07/01 to 06/13/01)
- 07 7 (06/14/01 to 06/20/01)
- 08 8 (06/21/01 to 06/27/01)
- 09 9 (06/28/01 to 07/04/01)
- 10 10 (07/05/01 to 07/11/01)
- 11 11 (07/12/01 to 07/18/01)
- 12 12 (07-19-01 to 07-25-01)
- 13 13 (07-26-01 to 08-01-01)
- 14 14 (08-02-01 to 08-08-01)
- 15 15 (08-09-01 to 08-15-01)
- 16 16 (08-16-01 to 08-22-01)
- 17 17 (08-23-01 to 08-29-01)
- 18 18 (08-30-01 to 09-05-01)
- 19 19 (09-06-01 to 09-12-01)
- 20 20 (09-13-01 to 09-19-01)
- 21 21 (09-20-01 to 09-26-01)
- 22 22 (09-27-01 to 10-03-01)
- 23 23 (10-04-01 to 10-10-01)
- 24 24 (10-11-01 to 10-17-01)
- 25 25 (10-18-01 to 10-24-01)
- 26 26 (10-25-01 to 10-31-01)
- 27 27 (11-01-01 to 11-07-01)
- 28 28 (11-08-01 to 11-14-01)
- 29 29 (11-15-01 to 11-21-01)
- 30 30 (11-22-01 to 11-28-01)
- 31 31 (11-29-01 to 12-05-01)
- 32 32 (12-06-01 to 12-12-01)
- 33 33 (12-13-01 to 12-19-01)
- 34 34 (12-20-01 to 12-26-01)
- 35 35 (12-27-01 to 01-02-02)
- 36 36 (01-03-02 to 01-09-02)
- 37 37 (01-10-02 to 01-16-02)

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

- 38 38 (01-17-02 to 01-23-02)
- 39 39 (01-24-02 to 01-30-02)
- 40 40 (01-31-02 to 02-06-02)
- 41 41 (02-07-02 to 02-13-02)
- 42 42 (02-14-02 to 02-20-02)
- 43 43 (02-21-02 to 02-27-02)
- 44 44 (02-28-02 to 03-06-02)
- 45 45 (03-07-02 to 03-13-02)
- 46 46 (03-14-02 to 03-20-02)
- 47 47 (03-21-02 to 03-27-02)
- 48 48 (03-28-02 to 04-03-02)
- 49 49 (04-04-02 to 04-10-02)
- 50 50 (04-11-02 to 04-17-02)
- 51 51 (04-18-02 to 04-24-02)

VARIABLE: WEEK FORMAT: WEEKNUM TYPE: N
SKIP CODE:

Address (where tester will go for site visit)

VARIABLE: header4 FORMAT: HEADER3 TYPE: H
SKIP CODE:

2 number and street

VARIABLE: PADDRS FORMAT: \$TEXT64 TYPE: A
SKIP CODE:

2 unit

VARIABLE: PADDRU FORMAT: \$TEXT32 TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

2 city

VARIABLE: PCITY

FORMAT: \$TEXT32

TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

2 state

- AK AK - Alaska
- AL AL - Alabama
- AR AR - Arkansas
- AZ AZ - Arizona
- CA CA - California
- CO CO - Colorado
- CT CT - Connecticut
- DC DC - District of Columbia
- DE DE - Delaware
- FL FL - Florida
- GA GA - Georgia
- HI HI - Hawaii
- IA IA - Iowa
- ID ID - Idaho
- IL IL - Illinois
- IN IN - Indiana
- KS KS - Kansas
- KY KY - Kentucky
- LA LA - Louisiana
- MA MA - Massachusetts
- MD MD - Maryland
- ME ME - Maine
- MI MI - Michigan
- MN MN - Minnesota
- MO MO - Missouri
- MS MS - Mississippi
- MT MT - Montana
- NC NC - North Carolina
- ND ND - North Dakota
- NE NE - Nebraska
- NH NH - New Hampshire
- NJ NJ - New Jersey
- NM NM - New Mexico
- NV NV - Nevada
- NY NY - New York
- OH OH - Ohio
- OK OK - Oklahoma

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

- OR OR - Oregon
- PA PA - Pennsylvania
- RI RI - Rhode Island
- SC SC - South Carolina
- SD SD - South Dakota
- TN TN - Tennessee
- TX TX - Texas
- UT UT - Utah
- VA VA - Virginia
- VT VT - Vermont
- WA WA - Washington
- WI WI - Wisconsin
- WV WV - West Virginia
- WY WY - Wyoming

VARIABLE: PSTATE FORMAT: \$STATE TYPE: A

SKIP CODE:

2 ZIP 00000

VARIABLE: PZIP FORMAT: \$ZIP TYPE: A

SKIP CODE:

3 Phone Number (000)000-0000

VARIABLE: PPHN1 FORMAT: PHONE TYPE: A

SKIP CODE:

3 Phone Number (000)000-0000

VARIABLE: PPHN2 FORMAT: PHONE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

4 Type of Approach

- 1 Call for appointment
 2 Drop-In

VARIABLE: PPRCH FORMAT: APRCH TYPE: N

SKIP CODE:

Type of Housing to Be Requested

VARIABLE: header14 FORMAT: HEADER3 TYPE: H

SKIP CODE:

5 Rental

- 1 Furnished
 2 Unfurnished

VARIABLE: PHMTYPR FORMAT: HMTYPR TYPE: N

SKIP CODE:

6 Highest Monthly Rent of Available Units

VARIABLE: PHMPRI FORMAT: HPRIR TYPE: N

SKIP CODE:

7 Number of bedrooms in advertised housing

VARIABLE: PBEDS FORMAT: BEDS TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

8 Household Composition

- 1 Single Adult
- 2 Single Female Adult, 1 Child
- 3 Married Couple, No Children
- 4 Married Couple, 1 Child
- 5 Married Couple, 2 Children (Same Gender)
- 6 Married Couple, 2 Children (Different Genders)
- 7 Married Couple, 3 Children

VARIABLE: PHHCOMP FORMAT: HHCOMP TYPE: N

SKIP CODE:

9 Minimum number of bedrooms acceptable for household

VARIABLE: PMINBED FORMAT: BEDS TYPE: N

SKIP CODE: pminbed();

10 Date housing is Needed (mm/dd/yy)

VARIABLE: PHNEED FORMAT: DATE TYPE: A

SKIP CODE:

What was the FINAL DISPOSITION of the Advance Call?

VARIABLE: header22 FORMAT: HEADER3 TYPE: H

SKIP CODE:

11 Status of call

- 2 Advance call completed
- 3 Advance call attempted, not completed

VARIABLE: PCSTAT FORMAT: ADVANCR TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

11 Future Assignment Status of Test

- 1 Test assigned
- 2 Test not assigned

VARIABLE: PASSN FORMAT: ASSN TYPE: N

SKIP CODE: `chk_chk_slct('PCSTAT','PASSN','PINEL','1');`

11 Ad is Ineligible Because

- 41 Outside of target area
- 42 Seasonal/temporary/vacation/short-term
- 46 Agency no longer in business
- 47 No address and incorrect phone number in ad
- 49 Agency already selected for same race tenure test
- 51 For Sale By Owner
- 52 Exceeds price range
- 53 Multi-unit structure for sale
- 54 Housing for Older Persons
- 56 Unimproved lot, to be constructed
- 57 Mobile Home Sale Through Dealership
- 61 Share situation
- 62 Apartment Locator Service
- 64 Sublet
- 66 Public/Subsidized housing development
- 67 No testers available to test housing provider
- 99 Other (Specify:)

VARIABLE: PINEL FORMAT: PINELR TYPE: N

SKIP CODE: `chk_slct_txt('PASSN','PINEL','PINELS','1');`

11 Other (Specify)

VARIABLE: PINELS FORMAT: \$TEXT64 TYPE: A

SKIP CODE: `slct_txt_slct('PINEL','PINELS','PNOTC','99');`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Rental

***If an Advance Call Is Not Completed (if required), a Test Cannot Be Conducted.**

VARIABLE: header29 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Test Released

1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

Transaction Type

R Rental

S Sales

VARIABLE: TRANTYPE FORMAT: \$TAFTYP TYPE: A

SKIP CODE:

Site

AG Augusta, GA

AH Anaheim, CA

BA Baltimore, MD

BU Buffalo, NY

CH Chicago, IL

CO Columbus, GA

DC Washington, DC

HN Honolulu, HI

HU Huntsville, AL

MB Mobile, AL

MI Miami, FL

MY Montgomery, AL

NS Nassau-Suffolk County, NY

NY New York, NY

OK Oakland, CA

PH Philadelphia, PA

PT Pittsburgh, PA

RO Rochester, NY

RV Riverside, CA

SD San Diego, CA

SF San Francisco, CA

SJ San Jose, CA

SV Savannah, GA

XX UI Internal Test Site

ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Housing Provider Information

VARIABLE: header2 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

Week

- 01 1 (05/03/01 to 05/09/01)
- 02 2 (05/10/01 to 05/16/01)
- 03 3 (05/17/01 to 05/23/01)
- 04 4 (05/24/01 to 05/30/01)
- 05 5 (05/31/01 to 06/06/01)
- 06 6 (06/07/01 to 06/13/01)
- 07 7 (06/14/01 to 06/20/01)
- 08 8 (06/21/01 to 06/27/01)
- 09 9 (06/28/01 to 07/04/01)
- 10 10 (07/05/01 to 07/11/01)
- 11 11 (07/12/01 to 07/18/01)
- 12 12 (07-19-01 to 07-25-01)
- 13 13 (07-26-01 to 08-01-01)
- 14 14 (08-02-01 to 08-08-01)
- 15 15 (08-09-01 to 08-15-01)
- 16 16 (08-16-01 to 08-22-01)
- 17 17 (08-23-01 to 08-29-01)
- 18 18 (08-30-01 to 09-05-01)
- 19 19 (09-06-01 to 09-12-01)
- 20 20 (09-13-01 to 09-19-01)
- 21 21 (09-20-01 to 09-26-01)
- 22 22 (09-27-01 to 10-03-01)
- 23 23 (10-04-01 to 10-10-01)
- 24 24 (10-11-01 to 10-17-01)
- 25 25 (10-18-01 to 10-24-01)
- 26 26 (10-25-01 to 10-31-01)
- 27 27 (11-01-01 to 11-07-01)
- 28 28 (11-08-01 to 11-14-01)
- 29 29 (11-15-01 to 11-21-01)
- 30 30 (11-22-01 to 11-28-01)
- 31 31 (11-29-01 to 12-05-01)
- 32 32 (12-06-01 to 12-12-01)
- 33 33 (12-13-01 to 12-19-01)
- 34 34 (12-20-01 to 12-26-01)
- 35 35 (12-27-01 to 01-02-02)
- 36 36 (01-03-02 to 01-09-02)
- 37 37 (01-10-02 to 01-16-02)

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

- 38 38 (01-17-02 to 01-23-02)
- 39 39 (01-24-02 to 01-30-02)
- 40 40 (01-31-02 to 02-06-02)
- 41 41 (02-07-02 to 02-13-02)
- 42 42 (02-14-02 to 02-20-02)
- 43 43 (02-21-02 to 02-27-02)
- 44 44 (02-28-02 to 03-06-02)
- 45 45 (03-07-02 to 03-13-02)
- 46 46 (03-14-02 to 03-20-02)
- 47 47 (03-21-02 to 03-27-02)
- 48 48 (03-28-02 to 04-03-02)
- 49 49 (04-04-02 to 04-10-02)
- 50 50 (04-11-02 to 04-17-02)
- 51 51 (04-18-02 to 04-24-02)

VARIABLE: WEEK FORMAT: WEEKNUM TYPE: N
SKIP CODE:

1 Name

VARIABLE: PPNAME FORMAT: \$TEXT64 TYPE: A
SKIP CODE:

Address

VARIABLE: header4 FORMAT: HEADER3 TYPE: H
SKIP CODE:

2 number and street

VARIABLE: PADDRS FORMAT: \$TEXT64 TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

2 unit #

VARIABLE: PADDRU FORMAT: \$TEXT32 TYPE: A
SKIP CODE:

2 city

VARIABLE: PCITY FORMAT: \$TEXT32 TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

2 state

- AK AK - Alaska
- AL AL - Alabama
- AR AR - Arkansas
- AZ AZ - Arizona
- CA CA - California
- CO CO - Colorado
- CT CT - Connecticut
- DC DC - District of Columbia
- DE DE - Delaware
- FL FL - Florida
- GA GA - Georgia
- HI HI - Hawaii
- IA IA - Iowa
- ID ID - Idaho
- IL IL - Illinois
- IN IN - Indiana
- KS KS - Kansas
- KY KY - Kentucky
- LA LA - Louisiana
- MA MA - Massachusetts
- MD MD - Maryland
- ME ME - Maine
- MI MI - Michigan
- MN MN - Minnesota
- MO MO - Missouri
- MS MS - Mississippi
- MT MT - Montana
- NC NC - North Carolina
- ND ND - North Dakota
- NE NE - Nebraska
- NH NH - New Hampshire
- NJ NJ - New Jersey
- NM NM - New Mexico
- NV NV - Nevada
- NY NY - New York
- OH OH - Ohio
- OK OK - Oklahoma

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

- OR OR - Oregon
- PA PA - Pennsylvania
- RI RI - Rhode Island
- SC SC - South Carolina
- SD SD - South Dakota
- TN TN - Tennessee
- TX TX - Texas
- UT UT - Utah
- VA VA - Virginia
- VT VT - Vermont
- WA WA - Washington
- WI WI - Wisconsin
- WV WV - West Virginia
- WY WY - Wyoming

VARIABLE: PSTATE FORMAT: \$STATE TYPE: A
SKIP CODE:

2 ZIP 00000

VARIABLE: PZIP FORMAT: \$ZIP TYPE: A
SKIP CODE:

3 Phone Number(s) (000)000-0000

VARIABLE: PPHN1 FORMAT: PHONE TYPE: A
SKIP CODE:

3 Phone Number(s) (000)000-0000

VARIABLE: PPHN2 FORMAT: PHONE TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

Type of Housing to Be Requested

VARIABLE: header14 FORMAT: HEADER3 TYPE: H

SKIP CODE:

5 Sales

- 1 Single Family
- 2 Condo
- 3 Mobile Home
- 4 Co-op

VARIABLE: PHMTYPS FORMAT: HMTYPS TYPE: N

SKIP CODE:

6 Housing Price

VARIABLE: PHMPRI FORMAT: HPRIS TYPE: N

SKIP CODE:

7 Number of bedrooms in advertised housing

VARIABLE: PBEDS FORMAT: BEDS TYPE: N

SKIP CODE:

8 Household Composition

- 1 Single Adult
- 2 Single Female Adult, 1 Child
- 3 Married Couple, No Children
- 4 Married Couple, 1 Child
- 5 Married Couple, 2 Children (Same Gender)
- 6 Married Couple, 2 Children (Different Genders)
- 7 Married Couple, 3 Children

VARIABLE: PHHCOMP FORMAT: HHCOMP TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

9 Minimum number of bedrooms acceptable for household

VARIABLE: PMINBED FORMAT: BEDS TYPE: N

SKIP CODE: pminbed();

VARIABLE: header22 FORMAT: HEADER3 TYPE: H

SKIP CODE:

11 Status of call

- 1 Advance call not necessary for this sales ad
- 2 Advance call completed
- 3 Advance call attempted, not completed

VARIABLE: PCSTAT FORMAT: ADVANC TYPE: N

SKIP CODE:

11 Future Assignment status of test

- 1 Test assigned
- 2 Test not assigned

VARIABLE: PASSN FORMAT: ASSN TYPE: N

SKIP CODE: chk_chk_slct('PCSTAT','PASSN','PINEL','2');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

PAF Sales

11 Ad is Ineligible Because

- 41 Outside of target area
- 42 Seasonal/temporary/vacation/short-term
- 46 Agency no longer in business
- 47 No address and incorrect phone number in ad
- 49 Agency already selected for same race tenure test
- 51 For Sale By Owner
- 52 Exceeds price range
- 53 Multi-unit structure for sale
- 54 Housing for Older Persons
- 56 Unimproved lot, to be constructed
- 57 Mobile Home Sale Through Dealership
- 61 Share situation
- 62 Apartment Locator Service
- 64 Sublet
- 66 Public/Subsidized housing development
- 67 No testers available to test housing provider
- 99 Other (Specify:)

VARIABLE: PINEL FORMAT: PINELS TYPE: N

SKIP CODE: chk_slct_txt('PASSN','PINEL','PINELS','1');

11 Other (Specify)

VARIABLE: PINELS FORMAT: \$TEXT64 TYPE: A

SKIP CODE: slct_txt_slct('PINEL','PINELS','PNOTC','99');

*If an Advance Call Is Not Completed (if required), a Test Cannot Be Conducted.

VARIABLE: header29 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Test Released

- 1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE: `document.record.HSITEAD.focus();`

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

TESTERID

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

RACEID

- 11 White 1
- 12 Black 1
- 13 Hispanic 1
- 14 Asian/Pacific Islander 1
- 17 American Indian 1
- 18 Don't know 1
- 21 White 2
- 22 Black 2
- 23 Hispanic 2
- 24 Asian/Pacific Islander 2
- 27 American Indian 2
- 28 Don't know 2
- 31 White 3
- 32 Black 3
- 33 Hispanic 3
- 34 Asian/Pacific Islander 3
- 37 American Indian 3
- 38 Don't know 3

VARIABLE: RACEID FORMAT: TRACEID TYPE: N

SKIP CODE:

SEQUENCE

VARIABLE: SEQRH FORMAT: integr TYPE: N

SKIP CODE: this.blur();

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

1 Full Address of Home

VARIABLE: HHEAD1 FORMAT: HEADER3 TYPE: H

SKIP CODE:

1 Street number and name

VARIABLE: HSITEAD FORMAT: \$TEXT64 TYPE: A

SKIP CODE:

1 street type

- 1 Avenue
- 2 Blvd
- 3 Circle
- 4 Court
- 5 Drive
- 6 Highway
- 7 Parkway
- 8 Lane
- 9 Street
- 10 Road
- 11 Place
- 12 Route
- 13 Terrace
- 14 Path

VARIABLE: HSITETYP FORMAT: STRTYP TYPE: N

SKIP CODE:

1 unit number

VARIABLE: HUNITNO FORMAT: \$text8 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

1 city

VARIABLE: HCITY

FORMAT: \$TEXT32

TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

1 state

- AK AK - Alaska
- AL AL - Alabama
- AR AR - Arkansas
- AZ AZ - Arizona
- CA CA - California
- CO CO - Colorado
- CT CT - Connecticut
- DC DC - District of Columbia
- DE DE - Delaware
- FL FL - Florida
- GA GA - Georgia
- HI HI - Hawaii
- IA IA - Iowa
- ID ID - Idaho
- IL IL - Illinois
- IN IN - Indiana
- KS KS - Kansas
- KY KY - Kentucky
- LA LA - Louisiana
- MA MA - Massachusetts
- MD MD - Maryland
- ME ME - Maine
- MI MI - Michigan
- MN MN - Minnesota
- MO MO - Missouri
- MS MS - Mississippi
- MT MT - Montana
- NC NC - North Carolina
- ND ND - North Dakota
- NE NE - Nebraska
- NH NH - New Hampshire
- NJ NJ - New Jersey
- NM NM - New Mexico
- NV NV - Nevada
- NY NY - New York
- OH OH - Ohio
- OK OK - Oklahoma

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

- OR OR - Oregon
- PA PA - Pennsylvania
- RI RI - Rhode Island
- SC SC - South Carolina
- SD SD - South Dakota
- TN TN - Tennessee
- TX TX - Texas
- UT UT - Utah
- VA VA - Virginia
- VT VT - Vermont
- WA WA - Washington
- WI WI - Wisconsin
- WV WV - West Virginia
- WY WY - Wyoming

VARIABLE: HSTATE FORMAT: \$STATE TYPE: A
SKIP CODE:

1 ZIP 00000

VARIABLE: HZIP FORMAT: \$ZIP TYPE: A
SKIP CODE:

2 Basic Information

VARIABLE: HHEAD2 FORMAT: HEADER3 TYPE: H
SKIP CODE:

2a Is this the advertised home?

- 1 Yes
- 0 No

VARIABLE: HADHOME FORMAT: yesno TYPE: N
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

2b Did you inspect the home?

- 1 Yes
 0 No

VARIABLE: HINSPCT FORMAT: yesno TYPE: N

SKIP CODE:

2c How many bedrooms were in the home?

VARIABLE: HBEDRMS FORMAT: BEDS TYPE: N

SKIP CODE:

2d What was the current asking price?

VARIABLE: HPRICE FORMAT: N8 TYPE: N

SKIP CODE:

2d What was the current asking price?

VARIABLE: HASKPRI FORMAT: N7 TYPE:

SKIP CODE:

3 What type of building is it?

- 1 Single-family detached
 2 Duplex
 3 Rowhouse or Townhouse
 4 Multi-family structure
 5 Mobile home

VARIABLE: HHMTYPE FORMAT: HMTYPH TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

4 Is this a newly built home that has never been occupied?

- 1 Yes
 0 No

VARIABLE: HHMNEW FORMAT: yesno TYPE: N

SKIP CODE:

5 How do you rate the physical condition of the home's INTERIOR?

- 1 Clean and in excellent repair, move in condition
 2 Some cleaning and minor maintenance needed, adequate
 3 Very dirty and in need of substantial maintenance,
 4 Not applicable (did not view or unit was a model)

VARIABLE: HINTCON FORMAT: CONDITN TYPE: N

SKIP CODE:

6 How do you rate the physical condition of the home's EXTERIOR?

- 1 Clean and in excellent repair, move in condition
 2 Some cleaning and minor maintenance needed, adequate
 3 Very dirty and in need of substantial maintenance,
 4 Not applicable (did not view or unit was a model)

VARIABLE: HEXTCN FORMAT: CONDITN TYPE: N

SKIP CODE:

7 Did the agent make any of the following comments about the surrounding neighborhood?

VARIABLE: HHEAD3 FORMAT: HEADER3 TYPE: H

SKIP CODE:

7a Noise

- 1 Quiet
 2 Noisy
 3 No comment

VARIABLE: HNOIS FORMAT: NOISE TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

7b Safety

- 1 Safe/low crime
- 2 Dangerous/high crime
- 3 No comment

VARIABLE: HSAFE FORMAT: SAFETY TYPE: N

SKIP CODE:

7c Schools

- 1 Good
- 2 Poor
- 3 No comment

VARIABLE: HSCHL FORMAT: SCHOOLS TYPE: N

SKIP CODE:

7d Investment

- 1 Rising values/good investment
- 2 Flat values/ not much appreciation
- 3 Declining values/depreciation
- 4 No comment

VARIABLE: HINVS FORMAT: invest TYPE: N

SKIP CODE:

7e Public Services

- 1 Good services/amenities
- 2 Poor/unreliable services
- 3 No comment

VARIABLE: HPUBS FORMAT: PUBSERV TYPE: N

SKIP CODE:

7f Race or ethnicity

- 1 Yes
- 0 No

VARIABLE: HRACE FORMAT: yesno TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

RecHomes

7f If yes, please record what the agent said about race or ethnicity:

VARIABLE: HRACETX FORMAT: \$text500 TYPE: A

SKIP CODE: `chk_txt_chk('HRACE','HRACETX','COMP',1);`

This form is complete

1 Yes

0 No

VARIABLE: COMP FORMAT: YESNO TYPE: N

SKIP CODE:

Delete this record (for TC use only)

1 Yes

0 No

VARIABLE: DELREC FORMAT: YESNO TYPE: N

SKIP CODE:

Test Released

1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A

SKIP CODE: `document.record.COMP[0].focus();`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rent Narr

Race ID

VARIABLE: RACEID

FORMAT: \$RACEID

TYPE:

SKIP CODE:

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE

FORMAT: \$SITE

TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rent Narr

Control Number

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Tester ID

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

Narrative

VARIABLE: NARRATIV FORMAT: \$BIGTXT TYPE: A

SKIP CODE:

This form is completed

- 1 Yes
 2 No

VARIABLE: COMP FORMAT: \$YESNO TYPE: A

SKIP CODE:

Released

- 1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

RACEID

- 11 White 1
- 12 Black 1
- 13 Hispanic 1
- 14 Asian/Pacific Islander 1
- 17 American Indian 1
- 18 Don't know 1
- 21 White 2
- 22 Black 2
- 23 Hispanic 2
- 24 Asian/Pacific Islander 2
- 27 American Indian 2
- 28 Don't know 2
- 31 White 3
- 32 Black 3
- 33 Hispanic 3
- 34 Asian/Pacific Islander 3
- 37 American Indian 3
- 38 Don't know 3

VARIABLE: RACEID FORMAT: TRACEID TYPE: N

SKIP CODE:

TESTER ID NUMBER:

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

1 Name of Test Site

VARIABLE: RSITENM FORMAT: \$text64 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

2 Address:

VARIABLE: HEADER70 FORMAT: HEADER3 TYPE: H

SKIP CODE:

2 Address (number & street)

VARIABLE: RSITENS FORMAT: \$text32 TYPE: A

SKIP CODE:

2 Street Type

- 1 Avenue
- 2 Blvd
- 3 Circle
- 4 Court
- 5 Drive
- 6 Highway
- 7 Parkway
- 8 Lane
- 9 Street
- 10 Road
- 11 Place
- 12 Route
- 13 Terrace
- 14 Path

VARIABLE: RSITETYP FORMAT: STRTYP TYPE: N

SKIP CODE:

2 Address: (unit #)

VARIABLE: RUNITNO FORMAT: \$text10 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

2 Address: (city)

VARIABLE: RSITECTY FORMAT: \$text32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

2 Address: (state)

- AK AK - Alaska
- AL AL - Alabama
- AR AR - Arkansas
- AZ AZ - Arizona
- CA CA - California
- CO CO - Colorado
- CT CT - Connecticut
- DC DC - District of Columbia
- DE DE - Delaware
- FL FL - Florida
- GA GA - Georgia
- HI HI - Hawaii
- IA IA - Iowa
- ID ID - Idaho
- IL IL - Illinois
- IN IN - Indiana
- KS KS - Kansas
- KY KY - Kentucky
- LA LA - Louisiana
- MA MA - Massachusetts
- MD MD - Maryland
- ME ME - Maine
- MI MI - Michigan
- MN MN - Minnesota
- MO MO - Missouri
- MS MS - Mississippi
- MT MT - Montana
- NC NC - North Carolina
- ND ND - North Dakota
- NE NE - Nebraska
- NH NH - New Hampshire
- NJ NJ - New Jersey
- NM NM - New Mexico
- NV NV - Nevada
- NY NY - New York
- OH OH - Ohio
- OK OK - Oklahoma

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

- OR OR - Oregon
- PA PA - Pennsylvania
- RI RI - Rhode Island
- SC SC - South Carolina
- SD SD - South Dakota
- TN TN - Tennessee
- TX TX - Texas
- UT UT - Utah
- VA VA - Virginia
- VT VT - Vermont
- WA WA - Washington
- WI WI - Wisconsin
- WV WV - West Virginia
- WY WY - Wyoming

VARIABLE: RSITEST FORMAT: \$state TYPE: A

SKIP CODE:

2 Address: (zip) 00000

VARIABLE: RSITEZIP FORMAT: \$zip TYPE: A

SKIP CODE:

3 Type of Visit:

- 1 Drop in
- 2 Call for appointment

VARIABLE: RVSTTYP FORMAT: VSTTYP TYPE: A

SKIP CODE:

4 Date and time of site visit

VARIABLE: HEAD140 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

4 Date and time of Site Visit: Date (mm/dd/yy)

VARIABLE: RVDATE FORMAT: date TYPE: A

SKIP CODE:

4 Date and time of Site Visit: Day of Week:

- 1 Monday
- 2 Tuesday
- 3 Wednesday
- 4 Thursday
- 5 Friday
- 6 Saturday
- 7 Sunday

VARIABLE: RVDAY FORMAT: day TYPE: N

SKIP CODE:

4 Appointment Time:

VARIABLE: Head170 FORMAT: HEADER3 TYPE: H

SKIP CODE:

4 Date and time of Site Visit: Appointment Time (_ : _)

VARIABLE: RBEGH FORMAT: \$HOUR TYPE: A

SKIP CODE:

4 Date and time of Site Visit: Appointment Time: AM/PM

- 1 AM
- 2 PM

VARIABLE: RBEGAM FORMAT: ampm TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

5a Time began (office arrival):

VARIABLE: Head210 FORMAT: HEADER3 TYPE: H

SKIP CODE:

5a Time began (arrival): (_ : _ : _)

VARIABLE: RBGNH FORMAT: \$HOUR TYPE: A

SKIP CODE:

5a Time began (arrival): AM/PM

1 AM

2 PM

VARIABLE: RBGNAM FORMAT: ampm TYPE: N

SKIP CODE:

5b Time ended (departure):

VARIABLE: Head250 FORMAT: HEADER3 TYPE: H

SKIP CODE:

5b Time ended (departure): (_ : _ : _)

VARIABLE: rendm FORMAT: \$HOUR TYPE: A

SKIP CODE:

5b Time ended (departure): AM/PM

1 AM

2 PM

VARIABLE: RENDAM FORMAT: ampm TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

Information on persons with whom you had contact during your visit [check responses where appropriate]

VARIABLE: HEAD195 FORMAT: HEADER3 TYPE: H

SKIP CODE:

6 1. Name:

VARIABLE: RAGNAME1 FORMAT: \$text32 TYPE: A

SKIP CODE:

6 1. Position:

VARIABLE: RAGPOS1 FORMAT: \$text32 TYPE: A

SKIP CODE:

6 1. Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: RAGRACE1 FORMAT: trace TYPE: N

SKIP CODE:

6 1. Gender

- 0 Female
- 1 Male

VARIABLE: RAGGEND1 FORMAT: sex TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

6 1. Age Group

- 1 18 to 30
- 2 31 to 45
- 3 46 to 65
- 4 Over 65

VARIABLE: RAGAGE1 FORMAT: agegp TYPE: N

SKIP CODE:

6 1. Primary Person Who Provided Info

- 1 Yes
- 0 No

VARIABLE: RAGMET1 FORMAT: yesno TYPE: N

SKIP CODE:

6 2. Name:

VARIABLE: RAGNAME2 FORMAT: \$text32 TYPE: A

SKIP CODE:

6 2. Position:

VARIABLE: RAGPOS2 FORMAT: \$text32 TYPE: A

SKIP CODE:

6 2. Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: RAGRACE2 FORMAT: trace TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

6 2. Gender

0 Female

1 Male

VARIABLE: RAGGEND2 FORMAT: sex TYPE: N

SKIP CODE:

6 2. Age Group

1 18 to 30

2 31 to 45

3 46 to 65

4 Over 65

VARIABLE: RAGAGE2 FORMAT: agegp TYPE: N

SKIP CODE:

6 2. Primary Person Who Provided Info

1 Yes

0 No

VARIABLE: RAGMET2 FORMAT: yesno TYPE: N

SKIP CODE:

6 3. Name:

VARIABLE: RAGNAME3 FORMAT: \$text32 TYPE: A

SKIP CODE:

6 3. Position:

VARIABLE: RAGPOS3 FORMAT: \$text32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

6 3. Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: RAGRACE3 FORMAT: trace TYPE: N

SKIP CODE:

6 3. Gender

- 0 Female
- 1 Male

VARIABLE: RAGGEND3 FORMAT: sex TYPE: N

SKIP CODE:

6 3. Age Group

- 1 18 to 30
- 2 31 to 45
- 3 46 to 65
- 4 Over 65

VARIABLE: RAGAGE3 FORMAT: agegp TYPE: N

SKIP CODE:

6 3. Primary Person Who Provided Info

- 1 Yes
- 0 No

VARIABLE: RAGMET3 FORMAT: yesno TYPE: N

SKIP CODE:

6 4. Name:

VARIABLE: RAGNAME4 FORMAT: \$text32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

6 4. Position:

VARIABLE: RAGPOS4 FORMAT: \$text32 TYPE: A

SKIP CODE:

6 4. Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: RAGRACE4 FORMAT: trace TYPE: N

SKIP CODE:

6 4. Gender

- 0 Female
- 1 Male

VARIABLE: RAGGEND4 FORMAT: sex TYPE: N

SKIP CODE:

6 4. Age Group

- 1 18 to 30
- 2 31 to 45
- 3 46 to 65
- 4 Over 65

VARIABLE: RAGAGE4 FORMAT: agegp TYPE: N

SKIP CODE:

6 4. Primary Person Who Provided Info

- 1 Yes
- 0 No

VARIABLE: RAGMET4 FORMAT: yesno TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

6 5. Name:

VARIABLE: RAGNAME5 FORMAT: \$text32 TYPE: A

SKIP CODE:

6 5. Position:

VARIABLE: RAGPOS5 FORMAT: \$text32 TYPE: A

SKIP CODE:

6 5. Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: RAGRACE5 FORMAT: trace TYPE: N

SKIP CODE:

6 5. Gender

- 0 Female
- 1 Male

VARIABLE: RAGGEND5 FORMAT: sex TYPE: N

SKIP CODE:

6 5. Age Group

- 1 18 to 30
- 2 31 to 45
- 3 46 to 65
- 4 Over 65

VARIABLE: RAGAGE5 FORMAT: AGEGP TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

6 5. Primary Person Who Provided Info

1 Yes

0 No

VARIABLE: RAGMET5 FORMAT: yesno TYPE: N

SKIP CODE:

7 Were you able to meet with an agent to discuss housing options?

1 Yes

0 No

VARIABLE: RMEETAG FORMAT: yesno TYPE: N

SKIP CODE:

7a If No, why not?

VARIABLE: RMEETAGS FORMAT: \$text128 TYPE: A

SKIP CODE: chk_txt_txt('RMEETAG','RMEETAGS','RWAITM','0');

8 How many minutes did you wait to meet with someone (I.e. between the time you were greeted by someone when you entered and the time you met with the agent)?

VARIABLE: RWAITM FORMAT: INTEGR TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

9 When you asked about the availability of the advertised housing, what were you told? [check only ONE box]

1 Housing is available when I need it

2 Housing is not available when I need it

3 The agent did not know the status of the house

4 Something else

VARIABLE: RAVLBAD FORMAT: AVLAD TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

9 Something else (specify):

VARIABLE: RAVLBADS FORMAT: \$text128 TYPE: A

SKIP CODE: slct_txt_chk('RAVLBAD','RAVLBADS','RSAMEBED','4');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)}. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

10 When you asked about "similar" housing, were you told that there was anything available? ["similar" housing has the same number of bedrooms as the advertised housing, is in your price range, and is available when you need it.]

- 1 Yes
 2 No
 3 Agent did not know

VARIABLE: RSAMEBED FORMAT: YNDK TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

10a If Yes, how many "similar" housing units were you told about? (Do not include advertised unit)

VARIABLE: RSAMEBS FORMAT: \$text2 TYPE: A

SKIP CODE: chk_txt_chk2('RSAMEBED','RSAMEBS','RMINBED','0');

11 Whether you asked or the agent offered, were you told that any "other" housing was available? ["Other" housing has at least the minimum number of bedrooms for your household, is in your price range, and is available when you need it.]

- 1 Yes
 2 No
 3 Agent did not know

VARIABLE: RMINBED FORMAT: YNDK TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

11a If Yes, how many "other" housing units were you told about?

VARIABLE: RMINBEDS FORMAT: \$text2 TYPE: A

SKIP CODE: chk_txt_txt2('RMINBED','RMINBEDS','RTOTUNIT','0');

12 TOTAL rental units the agent indicated were available to you (Q9,+Q10a+Q11a.)

VARIABLE: RTOTUNIT FORMAT: INTEGR TYPE: N

SKIP CODE: rentalScript(); return disallowR('RMEETAG','0',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

13 During your visit, did the agent comment on or make reference to any of the following: Fair Housing Laws, Equal Housing Opportunity, Open Housing Ordinance, or Anti-discrimination Laws?

1 Yes

0 No

VARIABLE: RAGFHLAW FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

13a If Yes, what was the comment or reference?

VARIABLE: RFHLAWTX FORMAT: \$text500 TYPE: A

SKIP CODE: chk_txt_chk2('RAGFHLAW','RFHLAWTX','RINVTAPP','0');

14 Were you invited to complete an application during your visit?

1 Yes

0 No

VARIABLE: RINVTAPP FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

14a Were you told an application is necessary before renting a unit?

1 Yes

0 No

VARIABLE: RAPPNEC FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

14b Were you invited to take an application with you?

1 Yes

0 No

VARIABLE: RINVTAPT FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

14c Were you told a credit check is necessary before renting a unit?

1 Yes

0 No

VARIABLE: RCREDCHK FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

14d Were you told a criminal background check is necessary before renting a unit?

1 Yes

0 No

VARIABLE: RCRIMCHK FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

Were any of the following qualifications to rent requested by the agent?

VARIABLE: RHEAD649 FORMAT: HEADER3 TYPE: H

SKIP CODE:

15 Your marital status

1 I volunteered

2 Agent requested

3 Obtained in earlier phone call

4 Agent did not obtain

VARIABLE: RQMARRY FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

15 Your family size

1 I volunteered

2 Agent requested

3 Obtained in earlier phone call

4 Agent did not obtain

VARIABLE: RQFAMSIZ FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

15 Your income

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: RQINCOME FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

15 Your spouse's income

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: RQSPINCM FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

15 Your occupation

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: RQOCCUP FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

15 Your spouse's occupation

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: RQSOCUP FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

15 Your length of employment

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: RQEMPLN FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

15 Your spouse's length of employment

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: RQSPEMP FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

15 Your credit standing

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: RQCREDIT FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

15 Other:

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: RQOTHER FORMAT: volreq TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

Specify

VARIABLE: RQOTHRs FORMAT: \$text32 TYPE: A

SKIP CODE: slct_txt_slct3('RQOTHER','RQOTHRs','RAGQUAL','2');

16 Did the agent make any of the following comments regarding your qualifications to rent?

- 1 You are qualified
- 2 You are NOT qualified
- 3 Qualifications Not Discussed

VARIABLE: RAGQUAL FORMAT: agqual TYPE: A

SKIP CODE: return disallowR('RMEETAG','0',this);

17 Did the agent suggest that you consider a different rental complex or building than the one in the ad?

- 1 Yes
- 0 No

VARIABLE: RSUGDIFF FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

17a If Yes, was the other property also managed by the same agency?

- 1 Yes
- 2 No
- 3 Agent did not know

VARIABLE: RDIFSAME FORMAT: yndk2 TYPE: N

SKIP CODE: chk_slct_chk('RSUGDIFF','RDIFSAME','RORACE','1');

18 Were any remarks made by the agent about race or ethnicity that were not associated with the neighborhoods in which recommended units were located?

- 1 Yes
- 0 No

VARIABLE: RORACE FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

18a If Yes, please record what the agent said:

VARIABLE: RORACET FORMAT: \$text500 TYPE: A

SKIP CODE: chk_txt_chk2('RORACE','RORACET','ROTRREM','0');

19 Were any remarks made by the agent about religion, persons with disabilities, or families with children?

1 Yes

0 No

VARIABLE: ROTRREM FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

19a If Yes, please record what the agent said:

VARIABLE: ROTRREM FORMAT: \$text500 TYPE: A

SKIP CODE: chk_txt_chk2('ROTRREM','ROTRREM','RCON1','0');

20 What arrangements were made regarding future contact between you and the agent [check all that apply]?

VARIABLE: HEAD815 FORMAT: HEADER3 TYPE: H

SKIP CODE: return disallowR('RMEETAG','0',this);

20 The agent said that he/she would contact you

1 Yes

0 No

VARIABLE: RCON1 FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

20 The agent invited you to call him/her

1 Yes

0 No

VARIABLE: RCON2 FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

20 Future arrangements were not made

1 Yes

0 No

VARIABLE: RFCON3 FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

20 Other

1 Yes

0 No

VARIABLE: RFCON4 FORMAT: yesno TYPE: N

SKIP CODE: return disallowR('RMEETAG','0',this);

20 Specify

VARIABLE: RFCON4S FORMAT: \$TEXT64 TYPE: A

SKIP CODE: chk_txt_chk('RFCON4','RFCON4S','COMP','1');

This form is complete

1 Yes

0 No

VARIABLE: COMP FORMAT: YESNO TYPE: N

SKIP CODE:

21 When was this report completed? Date (mm/dd/yy)

VARIABLE: RDATER FORMAT: DATE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Rental

21 When was this report completed? Day of Week

- 1 Monday
- 2 Tuesday
- 3 Wednesday
- 4 Thursday
- 5 Friday
- 6 Saturday
- 7 Sunday

VARIABLE: RDAYR FORMAT: DAY TYPE: N

SKIP CODE:

21 When was this report completed? Time (_ : _ : _)

VARIABLE: RTMRTH FORMAT: \$HOUR TYPE: A

SKIP CODE:

21 When was this report completed? Time AM/PM

- 1 AM
- 2 PM

VARIABLE: RTMRTAM FORMAT: AMPM TYPE: N

SKIP CODE:

Test Released

- 1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sale Narr

Site Code

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

Control Number

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sale Narr

Tester ID

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

Sales Sequence Number

VARIABLE: SEQUENCE FORMAT: \$TEXT2 TYPE: A

SKIP CODE:

Narrative

VARIABLE: NARRATIV FORMAT: \$BIGTXT TYPE: A

SKIP CODE:

This form is completed

- 1 Yes
 2 No

VARIABLE: COMP FORMAT: \$YESNO TYPE: A

SKIP CODE:

Released

- 1 Yes

VARIABLE: RELEASE FORMAT: YESONLY TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

RACEID

- 11 White 1
- 12 Black 1
- 13 Hispanic 1
- 14 Asian/Pacific Islander 1
- 17 American Indian 1
- 18 Don't know 1
- 21 White 2
- 22 Black 2
- 23 Hispanic 2
- 24 Asian/Pacific Islander 2
- 27 American Indian 2
- 28 Don't know 2
- 31 White 3
- 32 Black 3
- 33 Hispanic 3
- 34 Asian/Pacific Islander 3
- 37 American Indian 3
- 38 Don't know 3

VARIABLE: RACEID FORMAT: TRACEID TYPE: N

SKIP CODE:

Sequence

VARIABLE: SEQUENCE FORMAT: \$TEXT2 TYPE: A

SKIP CODE: `this.blur();`

TESTER ID NUMBER

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

1 Location of office

VARIABLE: head40 FORMAT: HEADER3 TYPE: H

SKIP CODE:

1 Firm Name (if applicable, if not, NA)

VARIABLE: SFRMNAME FORMAT: \$TEXT64 TYPE: A

SKIP CODE:

1 Office/Room Number:

VARIABLE: SFRMRM FORMAT: \$TEXT10 TYPE: A

SKIP CODE:

1 Address:

VARIABLE: HEADER70 FORMAT: HEADER3 TYPE: H

SKIP CODE:

1 Street number and name

VARIABLE: SFIRMSR FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

1 Street type

- 1 Avenue
- 2 Blvd
- 3 Circle
- 4 Court
- 5 Drive
- 6 Highway
- 7 Parkway
- 8 Lane
- 9 Street
- 10 Road
- 11 Place
- 12 Route
- 13 Terrace
- 14 Path

VARIABLE: SFIRMTPT

FORMAT: STRTYP

TYPE: N

SKIP CODE:

1 (city)

VARIABLE: SFIRMCTY

FORMAT: \$TEXT32

TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

1 State

- AK AK - Alaska
- AL AL - Alabama
- AR AR - Arkansas
- AZ AZ - Arizona
- CA CA - California
- CO CO - Colorado
- CT CT - Connecticut
- DC DC - District of Columbia
- DE DE - Delaware
- FL FL - Florida
- GA GA - Georgia
- HI HI - Hawaii
- IA IA - Iowa
- ID ID - Idaho
- IL IL - Illinois
- IN IN - Indiana
- KS KS - Kansas
- KY KY - Kentucky
- LA LA - Louisiana
- MA MA - Massachusetts
- MD MD - Maryland
- ME ME - Maine
- MI MI - Michigan
- MN MN - Minnesota
- MO MO - Missouri
- MS MS - Mississippi
- MT MT - Montana
- NC NC - North Carolina
- ND ND - North Dakota
- NE NE - Nebraska
- NH NH - New Hampshire
- NJ NJ - New Jersey
- NM NM - New Mexico
- NV NV - Nevada
- NY NY - New York
- OH OH - Ohio
- OK OK - Oklahoma

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

- OR OR - Oregon
- PA PA - Pennsylvania
- RI RI - Rhode Island
- SC SC - South Carolina
- SD SD - South Dakota
- TN TN - Tennessee
- TX TX - Texas
- UT UT - Utah
- VA VA - Virginia
- VT VT - Vermont
- WA WA - Washington
- WI WI - Wisconsin
- WV WV - West Virginia
- WY WY - Wyoming

VARIABLE: SFIRMST FORMAT: \$STATE TYPE: A

SKIP CODE:

1 (zip) 00000

VARIABLE: SFIRMZIP FORMAT: \$ZIP TYPE: A

SKIP CODE:

2 Date and time of site visit

VARIABLE: HEAD140 FORMAT: HEADER3 TYPE: H

SKIP CODE:

2 Date (mm/dd/yy)

VARIABLE: SAPPTD FORMAT: DATE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

2 Day of Week:

- 1 Monday
- 2 Tuesday
- 3 Wednesday
- 4 Thursday
- 5 Friday
- 6 Saturday
- 7 Sunday

VARIABLE: SAPPTDY FORMAT: DAY TYPE: N

SKIP CODE:

2 Appointment Time:

VARIABLE: Head170 FORMAT: HEADER3 TYPE: H

SKIP CODE:

2 Time (_ : _)

VARIABLE: SAPPTH FORMAT: \$HOUR TYPE: A

SKIP CODE:

2 (check box AM or PM)

- 1 AM
- 2 PM

VARIABLE: SAPPTAM FORMAT: AMPM TYPE: N

SKIP CODE:

2a Time began (office arrival):

VARIABLE: Head210 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

2a Time (_ : _)

VARIABLE: SBEGH FORMAT: \$HOUR TYPE: A
SKIP CODE:

2a AM/PM

1 AM
 2 PM

VARIABLE: SBEGAM FORMAT: AMPM TYPE: N
SKIP CODE:

2a Time ended (departure):

VARIABLE: Head250 FORMAT: HEADER3 TYPE: H
SKIP CODE:

2a Time (_ : _)

VARIABLE: SENDH FORMAT: \$HOUR TYPE: A
SKIP CODE:

2a AM/PM

1 AM
 2 PM

VARIABLE: SENDAM FORMAT: AMPM TYPE: N
SKIP CODE:

3 Is this your second site visit?

1 Yes
 0 No

VARIABLE: SSNDVIS FORMAT: YESNO TYPE: N
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

4 Information on persons with whom you had contact during your visit [check responses where appropriate]:

VARIABLE: Head310 FORMAT: HEADER3 TYPE: H

SKIP CODE:

4.1 Name:

VARIABLE: SAGNAME1 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

4.1 Position:

VARIABLE: SAGPOS1 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

4.1 Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: SAGRACE1 FORMAT: TRACE TYPE: N

SKIP CODE:

4.1 Gender

- 0 Female
- 1 Male

VARIABLE: SAGGEND1 FORMAT: SEX TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

4.1 Age Group

- 1 18 to 30
- 2 31 to 45
- 3 46 to 65
- 4 Over 65

VARIABLE: SAGAGE1 FORMAT: AGEGP TYPE: N

SKIP CODE:

4.1 Primary Person Who Provided Info

- 1 Yes
- 0 No

VARIABLE: SAGMETP1 FORMAT: YESNO TYPE: N

SKIP CODE:

4.2 Name:

VARIABLE: SAGNAME2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

4.2 Position:

VARIABLE: SAGPOS2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

4.2 Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: SAGRACE2 FORMAT: TRACE TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

4.2 Gender

0 Female

1 Male

VARIABLE: SAGGEND2 FORMAT: SEX TYPE: N

SKIP CODE:

4.2 Age Group

1 18 to 30

2 31 to 45

3 46 to 65

4 Over 65

VARIABLE: SAGAGE2 FORMAT: AGE GP TYPE: N

SKIP CODE:

4.2 Primary Person Who Provided Info

1 Yes

0 No

VARIABLE: SAGMETP2 FORMAT: YESNO TYPE: N

SKIP CODE:

4.3 Name:

VARIABLE: SAGNAME3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

4.3 Position:

VARIABLE: SAGPOS3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

4.3 Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: SAGRACE3 FORMAT: TRACE TYPE: N

SKIP CODE:

4.3 Gender

- 0 Female
- 1 Male

VARIABLE: SAGGEND3 FORMAT: SEX TYPE: N

SKIP CODE:

4.3 Age Group

- 1 18 to 30
- 2 31 to 45
- 3 46 to 65
- 4 Over 65

VARIABLE: SAGAGE3 FORMAT: AGE GP TYPE: N

SKIP CODE:

4.3 Primary Person Who Provided Info

- 1 Yes
- 0 No

VARIABLE: SAGMETP3 FORMAT: YESNO TYPE: N

SKIP CODE:

4.4 Name:

VARIABLE: SAGNAME4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

4.4 Position:

VARIABLE: SAGPOS4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

4.4 Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: SAGRACE4 FORMAT: TRACE TYPE: N

SKIP CODE:

4.4 Gender

- 0 Female
- 1 Male

VARIABLE: SAGGEND4 FORMAT: SEX TYPE: N

SKIP CODE:

4.4 Age Group

- 1 18 to 30
- 2 31 to 45
- 3 46 to 65
- 4 Over 65

VARIABLE: SAGAGE4 FORMAT: AGE GP TYPE: N

SKIP CODE:

4.4 Primary Person Who Provided Info

- 1 Yes
- 0 No

VARIABLE: SAGMETP4 FORMAT: YESNO TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

4.5 Name:

VARIABLE: SAGNAME5 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

4.5 Position:

VARIABLE: SAGPOS5 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

4.5 Race/Ethnicity (check one entry)

- 1 White
- 2 Black
- 3 Hispanic
- 4 Asian/Pacific Islander
- 7 American Indian
- 8 Don't know

VARIABLE: SAGRACE5 FORMAT: TRACE TYPE: N

SKIP CODE:

4.5 Gender

- 0 Female
- 1 Male

VARIABLE: SAGGEND5 FORMAT: SEX TYPE: N

SKIP CODE:

4.5 Age Group

- 1 18 to 30
- 2 31 to 45
- 3 46 to 65
- 4 Over 65

VARIABLE: SAGAGE5 FORMAT: AGE GP TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

4.5 Primary Person Who Provided Info

1 Yes

0 No

VARIABLE: SAGMETP5 FORMAT: YESNO TYPE: N

SKIP CODE:

5 Were you able to meet with an agent to discuss housing options?

1 Yes

0 No

VARIABLE: SAGMEETA FORMAT: YESNO TYPE: N

SKIP CODE:

5a If yes, where did you meet?

1 Agent's office

2 Somewhere else

VARIABLE: SWHRMEET FORMAT: WHRMEET TYPE: A

SKIP CODE: `chk_slct_txt('SAGMEETA','SWHRMEET','SWHRMETS','0');`

5a (specify)

VARIABLE: SWHRMETS FORMAT: \$TEXT64 TYPE: A

SKIP CODE: `slct_txt_txt('SWHRMEET','SWHRMETS','SNO MEET','2');`

5b If No, why not?

VARIABLE: SNO MEET FORMAT: \$TEXT128 TYPE: A

SKIP CODE: `chk_txt_chk('SAGMEETA','SNO MEET','SAGDECLN','0');`

6 Did the agent decline to meet with you today?

1 Yes

0 No

VARIABLE: SAGDECLN FORMAT: YESNO TYPE: N

SKIP CODE: `return disallows('SAGMEETA','0','SAGMEETA','0',this);`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

6a If yes, why?

VARIABLE: SAGDECLS FORMAT: \$TEXT128 TYPE: A

SKIP CODE: `chk_txt_txt('SAGDECLN','SAGDECLS','SWAITM','1');`

6a (NOTE: If you are able to make an appointment for a later time, then stop here and fill out the Site Visit Repc Form after your appointment)

VARIABLE: Head680 FORMAT: HEADER3 TYPE: H

SKIP CODE:

7 How many minutes did you wait to meet with someone (i.e. between the time you were greeted by someone at the firm when you entered and the time you met with an agent)? ____minutes

VARIABLE: SWAITM FORMAT: INTEGR TYPE: N

SKIP CODE: `return disallows('SAGMEETA','0','SAGDECLN','1',this);`

8 When you asked about the availability of the home in the Ad, what were you told? [check only ONE box]

- 1 Home is available
- 2 Home is not available
- 3 The agent did not know the status of the house.
- 4 Something else

VARIABLE: SAVLBAD FORMAT: AVLADS TYPE: A

SKIP CODE: `return disallows('SAGMEETA','0','SAGDECLN','1',this);`

8 Something else (specify):

VARIABLE: SAVLBADS FORMAT: \$TEXT64 TYPE: A

SKIP CODE: `slct_txt_chk('SAVLBAD','SAVLBADS','SSAMEBED','4');`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

9 Were you recommended any homes that were "similar" to the advertised home? [A "similar" home has the same number of bedrooms as the advertised home.]

- 1 Yes
 2 No
 3 Agent did not know

VARIABLE: SSAMEBED FORMAT: yndk TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

9a If yes, how many "similar" homes were recommended to you? (Do not include advertised home)

VARIABLE: SSAMEBS FORMAT: INTEGR TYPE: N

SKIP CODE: chk_txt_chk2('SSAMEBED','SSAMEBS','SMINBED','0');

10 Were you recommended any "other" homes? ["Other" homes have at least the minimum number of bedrooms for your household. "Other" housing also includes homes with a greater number of bedrooms than the advertised home.]

- 1 Yes
 2 No
 3 Agent did not know

VARIABLE: SMINBED FORMAT: yndk TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

10a If yes, how many "other" homes were recommended to you? ____ Homes

VARIABLE: SMINBEDS FORMAT: INTEGR TYPE: N

SKIP CODE: chk_txt_txt2('SMINBED','SMINBEDS','STOTUNIT','0');

11 How many TOTAL homes were recommended to you? (Number calculated from Qs 8, 9a, 10a)

VARIABLE: STOTUNIT FORMAT: INTEGR TYPE: N

SKIP CODE: salesScript();

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

12 How many homes were offered to you for your review in a listing or other format, BUT NOT SPECIFICALLY RECOMMENDED?

VARIABLE: STOTREV FORMAT: N4 TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

13 During your visit, did the agent comment on or make reference to any of the following: Fair Housing Laws, Equal Housing Opportunity, Open Housing Ordinance, or Anti-discrimination Law?

1 Yes

0 No

VARIABLE: SAGFHLAW FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

13a If yes, what was the comment or reference?

VARIABLE: SAGFHS FORMAT: \$TEXT500 TYPE: A

SKIP CODE: chk_txt_chk('SAGFHLAW','SAGFHS','SSRCMLB','1');

14 Based on your observations and the remarks of the agent, indicate below the sources used to select properties for your review: [check all that apply]

VARIABLE: Head800 FORMAT: HEADER3 TYPE: H

SKIP CODE:

14 None

1 Yes

0 No

VARIABLE: SSRNON FORMAT: yesno TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

14 Multiple listings book

1 Yes

0 No

VARIABLE: SSRMLB FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SSRCNON','SSRMLB','SSRCGMG','0');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

14 Home seeker guides/magazines

1 Yes

0 No

VARIABLE: SSRCGMG FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SSRCNON','SSRCGMG','SSRCPT','0');

14 Computer

1 Yes

0 No

VARIABLE: SSRCCPT FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SSRCNON','SSRCPT','SSRCWEB','0');

14 Internet website

1 Yes

0 No

VARIABLE: SSRWEB FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_txt('SSRCNON','SSRCWEB','SSRCWEBS','0');

14 Internet website - (specify):

VARIABLE: SSRWEBS FORMAT: \$TEXT64 TYPE: A

SKIP CODE: chk_txt_chk('SSRCWEB','SSRCWEBS','SSRCOPT','1');

14 Other printed sheet

1 Yes

0 No

VARIABLE: SSRCOPT FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SSRCNON','SSRCOPT','SSRCFCD','0');

14 File cards

1 Yes

0 No

VARIABLE: SSRFCFD FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SSRCNON','SSRCFCD','SSRCSR','0');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

14 Scraps of paper

1 Yes

0 No

VARIABLE: SSRCSRPF FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SSRCNON','SSRCSRPF','SSRCOTR','0');

14 Other

1 Yes

0 No

VARIABLE: SSRCOTR FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_txt('SSRCNON','SSRCOTR','SSRCOTRS','0');

14 Other (specify):

VARIABLE: SSRCOTRS FORMAT: \$TEXT64 TYPE: A

SKIP CODE: chk_txt_chk('SSRCOTR','SSRCOTRS','SREFAG','1');

15 Did one agent refer you to another agent who provided service to you?

1 Yes

0 No

VARIABLE: SREFAG FORMAT: YESNO TYPE: N

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

15a If yes, were you referred to an agent within the same agency?

1 Yes

0 No

VARIABLE: SREFSAME FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_txt('SREFAG','SREFSAME','SREFMETW','1');

15b If you were referred, using the numbers from question 4, enter the number of the person to whom you were referred.

VARIABLE: SREFMETW FORMAT: INTEGR TYPE: N

SKIP CODE: chk_txt_slct('SREFSAME','SREFMETW','SAGROLE','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

16 Was the agent's role described to you as being one of the following:

- 1 Buyer's agent
 2 Seller's agent
 3 Dual agent
 4 Did not disclose

VARIABLE: SAGROLE FORMAT: AGROLE TYPE: A

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

17 Were you asked to sign any agreements or documents? (Yes/No)

- 1 Yes
 0 No

VARIABLE: SSIGNDOC FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

17a If yes, please specify each below:

VARIABLE: Head970 FORMAT: HEADER3 TYPE: H

SKIP CODE:

17a Document Name

VARIABLE: SDOCNM11 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SSIGNDOC','SDOCNM11','SDOCPUR1','1');

17a Purpose

VARIABLE: SDOCPUR1 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_chk('SSIGNDOC','SDOCPUR1','SDOCS1','1');

17a Did you sign?

- 1 Yes
 0 No

VARIABLE: SDOCS1 FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_txt('SSIGNDOC','SDOCS1','SDOCNM2','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

17a Document Name

VARIABLE: SDOCNM2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SSIGNDOC','SDOCNM2','SDOCPUR2','1');

17a Purpose

VARIABLE: SDOCPUR2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_chk('SSIGNDOC','SDOCPUR2','SDOCS2','1');

17a Did you sign?

1 Yes

0 No

VARIABLE: SDOCS2 FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_txt('SSIGNDOC','SDOCS2','SDOCNM3','1');

17a Document Name

VARIABLE: SDOCNM3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SSIGNDOC','SDOCNM3','SDOCPUR3','1');

17a Purpose

VARIABLE: SDOCPUR3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_chk('SSIGNDOC','SDOCPUR3','SDOCS3','1');

17a Did you sign?

1 Yes

0 No

VARIABLE: SDOCS3 FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_txt('SSIGNDOC','SDOCS3','SDOCNM4','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

17a Document Name

VARIABLE: SDOCNM4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SSIGNDOC','SDOCNM4','SDOCPUR4','1');

17a Purpose

VARIABLE: SDOCPUR4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_chk('SSIGNDOC','SDOCPUR4','SDOCS4','1');

17a Did you sign?

1 Yes

0 No

VARIABLE: SDOCS4 FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SSIGNDOC','SDOCS4','SPREQ','1');

18 Did the agent ask if you had already visited a lender or been pre-qualified for financing?

1 Yes

0 No

VARIABLE: SPREQ FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

19 Did the agent REFUSE to show you any homes because you were not pre-qualified for financing?

1 Yes

0 No

VARIABLE: SREFPQ FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

20 Complete the grid below regarding any of your qualifications to purchase a house that were requested by th agent at any point. (check only one per line)

VARIABLE: Head1120 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

20 Your marital status

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQMARRY FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Your family size

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQFAMSIZ FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Your income

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQINCOME FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Your spouse's income

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQSPINCM FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

20 Your occupation

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQOCCUP FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Your spouse's occupation

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQSPOCC FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Your length of employment

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQEMPLNG FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Your spouses length of employment

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQSPEMPL FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

20 Your savings/assets (e.g. funds available for downpayment, closing costs, etc.)

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQASSET FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Your debts

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQDEBTS FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Credit standing

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQCREDIT FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Reason for moving

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQREASMV FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

20 Geographic preference

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQGEO FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Pre-qualification letter

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQPQLET FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 Other

- 1 I volunteered
- 2 Agent requested
- 3 Obtained in earlier phone call
- 4 Agent did not obtain

VARIABLE: SQOTHER FORMAT: volreq TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

20 (specify)

VARIABLE: SQOTRS FORMAT: \$TEXT64 TYPE: A

SKIP CODE: slct_txt_slct2('SQOTHER','SQOTRS','SAGQUAL','4');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

21 Which of the following comments were made regarding your qualifications to buy a home?

- 1 You are qualified
 2 You are NOT qualified
 3 Qualifications Not Discussed

VARIABLE: SAGQUAL FORMAT: AGQUAL TYPE: A

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

22 Did the agent volunteer to help you find financing?

- 1 Yes
 0 No

VARIABLE: SAGFINDF FORMAT: YESNO TYPE: N

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

23 Did the agent suggest one or more mortgage companies, lenders, or brokers?

- 1 Yes
 0 No

VARIABLE: SAGLNDR FORMAT: YESNO TYPE: N

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

23a If yes, please list them below:

VARIABLE: Head1320 FORMAT: HEADER3 TYPE: H

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

23a Mortgage Company/Firm

VARIABLE: SRMORT1 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNDR','SRMORT1','SRBROK1','1');

23a Lender/Broker Name

VARIABLE: SRBROK1 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNDR','SRBROK1','SRLCITY1','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

23a City

VARIABLE: SRLCITY1 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNDR','SRLCITY1','SRLPHON1','1');

23a Telephone (000)000-0000

VARIABLE: SRLPHON1 FORMAT: PHONE TYPE: A

SKIP CODE: chk_txt_txt('SAGLNDR','SRLPHON1','SRMORT2','1');

23a Mortgage Company/Firm

VARIABLE: SRMORT2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNDR','SRMORT2','SRBROK2','1');

23a Lender/Broker Name

VARIABLE: SRBROK2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNDR','SRBROK2','SRLCITY2','1');

23a City

VARIABLE: SRLCITY2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNDR','SRLCITY2','SRLPHON2','1');

23a Telephone (000)000-0000

VARIABLE: SRLPHON2 FORMAT: PHONE TYPE: A

SKIP CODE: chk_txt_txt('SAGLNDR','SRLPHON2','SRMORT3','1');

23a Mortgage Company/Firm

VARIABLE: SRMORT3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNDR','SRMORT3','SRBROK3','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

23a Lender/Broker Name

VARIABLE: SRBROK3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNR','SRBROK3','SRLCITY3','1');

23a City

VARIABLE: SRLCITY3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNR','SRLCITY3','SRLPHON3','1');

23a Telephone (000)000-0000

VARIABLE: SRLPHON3 FORMAT: PHONE TYPE: A

SKIP CODE: chk_txt_txt('SAGLNR','SRLPHON3','SRMORT4','1');

23a Mortgage Company/Firm

VARIABLE: SRMORT4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNR','SRMORT4','SRBROK4','1');

23a Lender/Broker Name

VARIABLE: SRBROK4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNR','SRBROK4','SRLCITY4','1');

23a City

VARIABLE: SRLCITY4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('SAGLNR','SRLCITY4','SRLPHON4','1');

23a Telephone (000)000-0000

VARIABLE: SRLPHON4 FORMAT: PHONE TYPE: A

SKIP CODE: chk_txt_chk('SAGLNR','SRLPHON4','SRTYPFIN','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

24 Did the agent discuss the type of financing that might be available to you?

1 Yes

0 No

VARIABLE: SRTYPFIN FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

24a If yes, please indicate which types of financing the agent discussed or mentioned by filling out the grid below: [check one per line]

VARIABLE: Head1500 FORMAT: HEADER3 TYPE: H

SKIP CODE:

24a Conventional Fixed Rate Financing (non FHA)

2 Agent did not mention

1 Agent discussed

VARIABLE: SRFIXED FORMAT: YNDIS TYPE: A

SKIP CODE: chk_slct_slct('SRTYPFIN','SRFIXED','SRARM','1');

24a Conventional Adjustable Rate Financing (ARM)

2 Agent did not mention

1 Agent discussed

VARIABLE: SRARM FORMAT: YNDIS TYPE: A

SKIP CODE: chk_slct_slct('SRTYPFIN','SRARM','SRFHAVA','1');

24a FHA or VA Financing

2 Agent did not mention

1 Agent discussed

VARIABLE: SRFHAVA FORMAT: YNDIS TYPE: A

SKIP CODE: chk_slct_slct('SRTYPFIN','SRFHAVA','SROTRGOV','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

24a Other government financing (state or local)

2 Agent did not mention

1 Agent discussed

VARIABLE: SROTRGOV FORMAT: YNDIS TYPE: A

SKIP CODE: chk_slct_txt('SRTPFIN','SROTRGOV','SRORGOVS','0');

24a (specify):

VARIABLE: SRORGOVS FORMAT: \$TEXT32 TYPE: A

SKIP CODE: slct_txt_slct('SROTRGOV','SRORGOVS','SROTRFIN','0');

24a Other

2 Agent did not mention

1 Agent discussed

VARIABLE: SROTRFIN FORMAT: YNDIS TYPE: A

SKIP CODE: chk_slct_txt('SRTPFIN','SROTRFIN','SRORFINS','0');

24a (specify)

VARIABLE: SRORFINS FORMAT: \$TEXT32 TYPE: A

SKIP CODE: slct_txt_chk('SROTRFIN','SRORFINS','SPREQUAL','0');

25 During the visit, did anyone pre-qualify you or calculate for you the amount of financing that you could afford using your specific financial information (income, debts, and assets)?

1 Yes

0 No

VARIABLE: SPREQUAL FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

25a If yes, using the numbers from Question 4, enter the number of the person who provided you with the information on the amount of financing you could afford: [enter line number]

VARIABLE: SPREQUAG FORMAT: integr TYPE: N

SKIP CODE: chk_txt_chk('SPREQUAL','SPREQUAG','SPREQAGR','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

25b If yes, was this person?

- 1 The agent who was providing information to you
- 2 An in-house mortgage specialist
- 3 A lender by telephone
- 4 Someone else

VARIABLE: SPREQAGR FORMAT: PREQAG TYPE: A

SKIP CODE: `chk_slct_chk('SPREQUAL','SPREQAGR','SSUGPRIC','1');`

26 Home Price: Did the agent suggest a house price or price range that you should consider?

- 1 Yes
- 0 No

VARIABLE: SSUGPRIC FORMAT: YESNO TYPE: N

SKIP CODE: `return disallowS('SAGMEETA','0','SAGDECLN','1',this);`

26a If yes, what was the total home price?

VARIABLE: Head1620 FORMAT: HEADER3 TYPE: H

SKIP CODE:

26a lowest

VARIABLE: SPRICLOW FORMAT: N8 TYPE: N

SKIP CODE: `chk_txt_txt('SSUGPRIC','SPRICLOW','SPRICHI','1');`

26a highest

VARIABLE: SPRICHI FORMAT: N8 TYPE: N

SKIP CODE: `chk_txt_chk('SSUGPRIC','SPRICHI','SSUGMORT','1');`

27 Loan/Mortgage Amount: Did the agent suggest a mortgage amount (\$ borrowed) or range that you should consider?

- 1 Yes
- 0 No

VARIABLE: SSUGMORT FORMAT: YESNO TYPE: N

SKIP CODE: `return disallowS('SAGMEETA','0','SAGDECLN','1',this);`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

27a If yes, what was the total loan amount?

VARIABLE: Head1660 FORMAT: HEADER3 TYPE: H

SKIP CODE:

27a lowest mortgage amount

VARIABLE: SMORTLOW FORMAT: n8 TYPE: N

SKIP CODE: chk_txt_txt('SSUGMORT','SMORTLOW','SMORTH','1');

27a highest mortgage amount

VARIABLE: SMORTH FORMAT: n8 TYPE: N

SKIP CODE: chk_txt_chk('SSUGMORT','SMORTH','SSUGRATE','1');

28 Interest Rates: Did the agent mention interest rates for mortgage loans?

1 Yes

0 No

VARIABLE: SSUGRATE FORMAT: YESNO TYPE: N

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

28a If yes, what were the interest rates mentioned?

VARIABLE: Head1700 FORMAT: HEADER3 TYPE: H

SKIP CODE:

28a lowest percentage

VARIABLE: SRATELOW FORMAT: float TYPE: N

SKIP CODE: chk_txt_txt('SSUGRATE','SRATELOW','SRATEHI','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

28a highest percentage

VARIABLE: SRATEHI FORMAT: float TYPE: N

SKIP CODE: chk_txt_chk('SSUGRATE','SRATEHI','SSUGPAY','1');

29 Monthly Payments: Did the agent mention monthly payments for a mortgage loan?

1 Yes

0 No

VARIABLE: SSUGPAY FORMAT: YESNO TYPE: N

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

29a If yes, what were the monthly payments?

VARIABLE: Head1740 FORMAT: HEADER3 TYPE: H

SKIP CODE:

29a lowest monthly payment

VARIABLE: SPAYLOW FORMAT: n5 TYPE: N

SKIP CODE: chk_txt_txt('SSUGPAY','SPAYLOW','SPAYHI','1');

29a highest monthly payment

VARIABLE: SPAYHI FORMAT: n5 TYPE: N

SKIP CODE: chk_txt_chk('SSUGPAY','SPAYHI','SSUGDOWN','1');

30 Downpayment: Did the agent mention the likely downpayment amount or percentage?

1 Yes

0 No

VARIABLE: SSUGDOWN FORMAT: YESNO TYPE: N

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

30a If yes, what was the downpayment amount or percentage?

VARIABLE: Head1780 FORMAT: HEADER3 TYPE: H

SKIP CODE:

30a lowest downpayment amount

VARIABLE: SDWNLOWA FORMAT: n8 TYPE: N

SKIP CODE: chk_txt_txt('SSUGDOWN','SDWNLOWA','SDWNHIA','1');

30a highest downpayment amount

VARIABLE: SDWNHIA FORMAT: n8 TYPE: N

SKIP CODE: chk_txt_txt('SSUGDOWN','SDWNHIA','SDWNLOWP','1');

30a lowest downpayment percent

VARIABLE: SDWNLOWP FORMAT: float TYPE: N

SKIP CODE: chk_txt_txt('SSUGDOWN','SDWNLOWP','SDWNHIP','1');

30a highest downpayment percent

VARIABLE: SDWNHIP FORMAT: float TYPE: N

SKIP CODE: chk_txt_chk('SSUGDOWN','SDWNHIP','SAGPYDN','1');

31 Did the agent discuss any of the following with you? (check all that apply)

VARIABLE: HEAD1830 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

31 None of the below were discussed

1 Yes

0 No

VARIABLE: SAGNODS FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

31 Paying down debts

1 Yes

0 No

VARIABLE: SAGPYDN FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SAGNODS','SAGPYDN','SAGDBCN','0');

31 Debt consolidation

1 Yes

0 No

VARIABLE: SAGDBCN FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SAGNODS','SAGDBCN','SAGASST','0');

31 Downpayment assistance (gift, special program)

1 Yes

0 No

VARIABLE: SAGASST FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SAGNODS','SAGASST','SAGCOSN','0');

31 Co-signer

1 Yes

0 No

VARIABLE: SAGCOSN FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SAGNODS','SAGCOSN','SAGSELA','0');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

31 Seller assistance

1 Yes

0 No

VARIABLE: SAGSELA FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('SAGNODS','SAGSELA','SAGPRQU','0');

31 Pre-qualification letter

1 Yes

0 No

VARIABLE: SAGPRQU FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_txt('SAGNODS','SAGPRQU','SAGSTX','0');

31a For any items discussed, please describe what you were told:

VARIABLE: SAGSTX FORMAT: \$TEXT500 TYPE: A

SKIP CODE: chk_txt_chk('SAGNODS','SAGSTX','SAGORC','0');

32 Did the agent discuss or make any comments about specific neighborhoods or geographic areas that were not associated with any recommended homes?

1 Yes

0 No

VARIABLE: SAGORC FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

33 Were any remarks made by the agent about race or ethnicity that were not associated with particular homes or neighborhoods?

1 Yes

0 No

VARIABLE: SAGORCR FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

33a If Yes, please record what the agent said:

VARIABLE: SAGORTX FORMAT: \$TEXT500 TYPE: A

SKIP CODE: chk_txt_chk('SAGORCR','SAGORTX','SAGRELC','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

34 Were any remarks made by the agent about religion, persons with disabilities, or families with children?

1 Yes

0 No

VARIABLE: SAGRELC FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

34a If Yes, please record what the agent said:

VARIABLE: SAGRELT FORMAT: \$TEXT500 TYPE: A

SKIP CODE: chk_txt_chk('SAGRELC','SAGRELT','SARNGM1','1');

35 What arrangements were made regarding future contact between you and the agent? [check all that apply]

VARIABLE: HEAD1970 FORMAT: HEADER3 TYPE: H

SKIP CODE:

35 The agent said that he/she would contact you

1 Yes

0 No

VARIABLE: SARNGM1 FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

35 The agent invited you to call him/her

1 Yes

0 No

VARIABLE: SARNGM2 FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

35 Made next appointment before leaving?

1 Yes

0 No

VARIABLE: SARNGM5 FORMAT: YESNO TYPE: N

SKIP CODE: return disallowS('SAGMEETA','0','SAGDECLN','1',this);

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

35 Future arrangements were not made

1 Yes

0 No

VARIABLE: SARNGM3 FORMAT: YESNO TYPE: N

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

35 Other

1 Yes

0 No

VARIABLE: SARNGM4 FORMAT: YESNO TYPE: N

SKIP CODE: return disallows('SAGMEETA','0','SAGDECLN','1',this);

35 Specify

VARIABLE: SARNGMS FORMAT: \$TEXT64 TYPE: A

SKIP CODE: chk_txt_chk('SARNGM4','SARNGMS','COMP','1');

36 When was this report completed?

VARIABLE: HEAD2030 FORMAT: HEADER3 TYPE: H

SKIP CODE:

This form is complete

1 Yes

0 No

VARIABLE: COMP FORMAT: YESNO TYPE: N

SKIP CODE:

36 Date (mm/dd/yy)

VARIABLE: SRDATE FORMAT: DATE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Sales

36 Day of Week

- 1 Monday
- 2 Tuesday
- 3 Wednesday
- 4 Thursday
- 5 Friday
- 6 Saturday
- 7 Sunday

VARIABLE: SRDAY

FORMAT: DAY

TYPE: N

SKIP CODE:

36 Time (_ : _)

VARIABLE: SRHR

FORMAT: \$HOUR

TYPE: A

SKIP CODE:

36 AM/PM

- 1 AM
- 2 PM

VARIABLE: SRAM

FORMAT: AMPM

TYPE: N

SKIP CODE:

Test Released

- 1 Yes

VARIABLE: RELEASE

FORMAT: YESONLY

TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAF

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

Transaction Type

- R Rental
- S Sales

VARIABLE: TRANTYPE FORMAT: \$TAFTYP TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAF

Week

- 01 1 (05/03/01 to 05/09/01)
- 02 2 (05/10/01 to 05/16/01)
- 03 3 (05/17/01 to 05/23/01)
- 04 4 (05/24/01 to 05/30/01)
- 05 5 (05/31/01 to 06/06/01)
- 06 6 (06/07/01 to 06/13/01)
- 07 7 (06/14/01 to 06/20/01)
- 08 8 (06/21/01 to 06/27/01)
- 09 9 (06/28/01 to 07/04/01)
- 10 10 (07/05/01 to 07/11/01)
- 11 11 (07/12/01 to 07/18/01)
- 12 12 (07-19-01 to 07-25-01)
- 13 13 (07-26-01 to 08-01-01)
- 14 14 (08-02-01 to 08-08-01)
- 15 15 (08-09-01 to 08-15-01)
- 16 16 (08-16-01 to 08-22-01)
- 17 17 (08-23-01 to 08-29-01)
- 18 18 (08-30-01 to 09-05-01)
- 19 19 (09-06-01 to 09-12-01)
- 20 20 (09-13-01 to 09-19-01)
- 21 21 (09-20-01 to 09-26-01)
- 22 22 (09-27-01 to 10-03-01)
- 23 23 (10-04-01 to 10-10-01)
- 24 24 (10-11-01 to 10-17-01)
- 25 25 (10-18-01 to 10-24-01)
- 26 26 (10-25-01 to 10-31-01)
- 27 27 (11-01-01 to 11-07-01)
- 28 28 (11-08-01 to 11-14-01)
- 29 29 (11-15-01 to 11-21-01)
- 30 30 (11-22-01 to 11-28-01)
- 31 31 (11-29-01 to 12-05-01)
- 32 32 (12-06-01 to 12-12-01)
- 33 33 (12-13-01 to 12-19-01)
- 34 34 (12-20-01 to 12-26-01)
- 35 35 (12-27-01 to 01-02-02)
- 36 36 (01-03-02 to 01-09-02)
- 37 37 (01-10-02 to 01-16-02)

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)}. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAF

- 38 38 (01-17-02 to 01-23-02)
- 39 39 (01-24-02 to 01-30-02)
- 40 40 (01-31-02 to 02-06-02)
- 41 41 (02-07-02 to 02-13-02)
- 42 42 (02-14-02 to 02-20-02)
- 43 43 (02-21-02 to 02-27-02)
- 44 44 (02-28-02 to 03-06-02)
- 45 45 (03-07-02 to 03-13-02)
- 46 46 (03-14-02 to 03-20-02)
- 47 47 (03-21-02 to 03-27-02)
- 48 48 (03-28-02 to 04-03-02)
- 49 49 (04-04-02 to 04-10-02)
- 50 50 (04-11-02 to 04-17-02)
- 51 51 (04-18-02 to 04-24-02)

VARIABLE: WEEK

FORMAT: WEEKNUM

TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Organization Name

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: ORGNAME FORMAT: \$SITE TYPE: A

SKIP CODE: document.record.ISSUEDTE.focus();

Issue Date (mm/dd/yy)

VARIABLE: ISSUEDTE FORMAT: DATE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAF

Regular Tests

VARIABLE: HEADER01 FORMAT: HEADER2 TYPE: H

SKIP CODE:

VARIABLE: TABHEAD1 FORMAT: THEADER TYPE: H

SKIP CODE:

Number

VARIABLE: TABHEAD2 FORMAT: THEADER TYPE: H

SKIP CODE:

Start

VARIABLE: TABHEAD4 FORMAT: THEADER TYPE: H

SKIP CODE:

Black/White tests

VARIABLE: RBWNUM FORMAT: INTEGR TYPE: N

SKIP CODE:

Start # for Black/White tests

VARIABLE: RBWSTART FORMAT: INTEGRS TYPE: N

SKIP CODE:

Asian/White tests

VARIABLE: RAWNUM FORMAT: INTEGR TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAF

Start # for Asian/White tests

VARIABLE: RAWSTART FORMAT: INTEGRS TYPE: N

SKIP CODE:

Hispanic/White tests

VARIABLE: RHWNUM FORMAT: INTEGR TYPE: N

SKIP CODE:

Start # for Hispanic/White tests

VARIABLE: RHWSTART FORMAT: INTEGRS TYPE: N

SKIP CODE:

Native American/White tests

VARIABLE: RNWNUM FORMAT: INTEGR TYPE: N

SKIP CODE:

Start # for Native American/White tests

VARIABLE: RNWSTART FORMAT: INTEGRS TYPE: N

SKIP CODE:

Triad Tests

VARIABLE: HEADER15 FORMAT: HEADER2 TYPE: H

SKIP CODE:

VARIABLE: TABHEAD5 FORMAT: THEADER TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAF

Number

VARIABLE: TABHEAD6 FORMAT: THEADER TYPE: H

SKIP CODE:

Start

VARIABLE: TABHEAD7 FORMAT: THEADER TYPE: H

SKIP CODE:

Black/White tests

VARIABLE: SBWNUM FORMAT: INTEGR TYPE: N

SKIP CODE:

Start # for Black/White tests

VARIABLE: SBWSTART FORMAT: INTEGRS TYPE: N

SKIP CODE:

Asian/White tests

VARIABLE: SAWNUM FORMAT: INTEGR TYPE: N

SKIP CODE:

Start # for Asian/White tests

VARIABLE: SAWSTART FORMAT: INTEGRS TYPE: N

SKIP CODE:

Hispanic/White tests

VARIABLE: SHWNUM FORMAT: INTEGR TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAF

Start # for Hispanic/White tests

VARIABLE: SHWSTART FORMAT: INTEGRS TYPE: N

SKIP CODE:

Native American/White tests

VARIABLE: SNWNUM FORMAT: INTEGR TYPE: N

SKIP CODE:

Start # for Native American/White tests

VARIABLE: SNWSTART FORMAT: INTEGRS TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Rental

Transaction Type

R Rental

S Sales

VARIABLE: TRANTYPE FORMAT: \$TAFTYP TYPE: A

SKIP CODE:

Site

AG Augusta, GA

AH Anaheim, CA

BA Baltimore, MD

BU Buffalo, NY

CH Chicago, IL

CO Columbus, GA

DC Washington, DC

HN Honolulu, HI

HU Huntsville, AL

MB Mobile, AL

MI Miami, FL

MY Montgomery, AL

NS Nassau-Suffolk County, NY

NY New York, NY

OK Oakland, CA

PH Philadelphia, PA

PT Pittsburgh, PA

RO Rochester, NY

RV Riverside, CA

SD San Diego, CA

SF San Francisco, CA

SJ San Jose, CA

SV Savannah, GA

XX UI Internal Test Site

ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Rental

VARIABLE: WEEK FORMAT: INTEGR TYPE: N
SKIP CODE:

Ad Number

VARIABLE: AD_NO FORMAT: NO3 TYPE: N
SKIP CODE:

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A
SKIP CODE:

Date of Issuance (mm/dd/yy)

VARIABLE: ISSUEDTE FORMAT: DATE TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Rental

Organization

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: ORGNAME FORMAT: \$SITE TYPE: A

SKIP CODE:

Sampler Code

VARIABLE: SAMPNAME FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Rental

Testing Type

- 1 Black/White
- 2 Hispanic/White
- 3 Asian/White
- 4 Native American/White
- 5 Black/White Triad
- 6 Hispanic/White Triad
- 7 Asian/White Triad
- 8 Native American/White Triad

VARIABLE: TESTTYPE FORMAT: TEST TYPE: N

SKIP CODE:

Required Sequence

- 1 Minority-White
- 2 White-Minority
- 3 Minority - White - White
- 4 White - Minority - Minority

VARIABLE: SEQUENCE FORMAT: SEQUENCE TYPE: N

SKIP CODE:

Narrative Required

- 1 Yes
- 0 No

VARIABLE: NARRATIV FORMAT: YESNO TYPE: N

SKIP CODE:

Unit Type

- 1 Unfurnished
- 2 Furnished

VARIABLE: UNITYPE FORMAT: UNITYPR TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Rental

Source Type

- 1 Major Metropolitan Newspaper
- 2 Community Newspaper
- 3 Rental/Sales Guide
- 4 Internet

VARIABLE: SRCETYPE FORMAT: STYPE TYPE: N

SKIP CODE:

Date the Ad appeared (mm/dd/yy)

VARIABLE: ADDATE FORMAT: DATE TYPE: A

SKIP CODE:

Source Name

VARIABLE: SRCENAME FORMAT: SNAME TYPE: N

SKIP CODE:

Edition (if applicable)

VARIABLE: EDITION FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Location of Ad (Page, Column, Etc)

VARIABLE: GEOG FORMAT: \$ADTEXT TYPE: A

SKIP CODE:

Text of Ad

VARIABLE: ADTEXT FORMAT: \$BIGTXT TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Rental

Editor Name

VARIABLE: EDITNAME FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Release this test?

1 Yes

2 No

VARIABLE: RELEASE FORMAT: \$YESNO TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Sales

Transaction Type

R Rental

S Sales

VARIABLE: TRANTYPE FORMAT: \$TAFTYP TYPE: A

SKIP CODE:

Site

AG Augusta, GA

AH Anaheim, CA

BA Baltimore, MD

BU Buffalo, NY

CH Chicago, IL

CO Columbus, GA

DC Washington, DC

HN Honolulu, HI

HU Huntsville, AL

MB Mobile, AL

MI Miami, FL

MY Montgomery, AL

NS Nassau-Suffolk County, NY

NY New York, NY

OK Oakland, CA

PH Philadelphia, PA

PT Pittsburgh, PA

RO Rochester, NY

RV Riverside, CA

SD San Diego, CA

SF San Francisco, CA

SJ San Jose, CA

SV Savannah, GA

XX UI Internal Test Site

ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Sales

VARIABLE: WEEK FORMAT: INTEGR TYPE: N
SKIP CODE:

Ad Number

VARIABLE: AD_NO FORMAT: NO3 TYPE: N
SKIP CODE:

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A
SKIP CODE:

Date of Issuance (mm/dd/yy)

VARIABLE: ISSUEDTE FORMAT: DATE TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Sales

Organization

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: ORGNAME FORMAT: \$SITE TYPE: A

SKIP CODE:

Sampler Code

VARIABLE: SAMPNAME FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Sales

Testing Type

- 1 Black/White
- 2 Hispanic/White
- 3 Asian/White
- 4 Native American/White
- 5 Black/White Triad
- 6 Hispanic/White Triad
- 7 Asian/White Triad
- 8 Native American/White Triad

VARIABLE: TESTTYPE FORMAT: TEST TYPE: N

SKIP CODE:

Required Sequence

- 1 Minority-White
- 2 White-Minority
- 3 Minority - White - White
- 4 White - Minority - Minority

VARIABLE: SEQUENCE FORMAT: SEQUENCE TYPE: N

SKIP CODE:

Narrative Required

- 1 Yes
- 0 No

VARIABLE: NARRATIV FORMAT: YESNO TYPE: N

SKIP CODE:

Unit Type

- 3 Single Family Home
- 4 Condo
- 5 Co-op
- 6 Mobile Home

VARIABLE: UNITYPE FORMAT: UNITYTYP TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Sales

Source Type

- 1 Major Metropolitan Newspaper
- 2 Community Newspaper
- 3 Rental/Sales Guide
- 4 Internet

VARIABLE: SRCETYPE FORMAT: STYPE TYPE: N

SKIP CODE:

Date the Ad appeared (mm/dd/yy)

VARIABLE: ADDATE FORMAT: DATE TYPE: A

SKIP CODE:

Source Name

VARIABLE: SRCENAME FORMAT: SNAME TYPE: N

SKIP CODE:

Edition (if applicable)

VARIABLE: EDITION FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Location of Ad (Page, Column, Etc)

VARIABLE: GEOG FORMAT: \$ADTEXT TYPE: A

SKIP CODE:

Text of Ad

VARIABLE: ADTEXT FORMAT: \$BIGTXT TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Taf Sales

Editor Name

VARIABLE: EDITNAME FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Release this test?

1 Yes

2 No

VARIABLE: RELEASE FORMAT: \$YESNO TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFRental TC

Transaction Type

R Rental

S Sales

VARIABLE: TRANTYPE FORMAT: \$TAFTYP TYPE: A

SKIP CODE:

Site

AG Augusta, GA

AH Anaheim, CA

BA Baltimore, MD

BU Buffalo, NY

CH Chicago, IL

CO Columbus, GA

DC Washington, DC

HN Honolulu, HI

HU Huntsville, AL

MB Mobile, AL

MI Miami, FL

MY Montgomery, AL

NS Nassau-Suffolk County, NY

NY New York, NY

OK Oakland, CA

PH Philadelphia, PA

PT Pittsburgh, PA

RO Rochester, NY

RV Riverside, CA

SD San Diego, CA

SF San Francisco, CA

SJ San Jose, CA

SV Savannah, GA

XX UI Internal Test Site

ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFRental TC

VARIABLE: WEEK FORMAT: INTEGR TYPE: N
SKIP CODE:

Ad Number

VARIABLE: AD_NO FORMAT: NO3 TYPE: N
SKIP CODE:

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A
SKIP CODE:

Date of Issuance (mm/dd/yy)

VARIABLE: ISSUEDTE FORMAT: DATE TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFRental TC

Organization

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: ORGNAME FORMAT: \$SITE TYPE: A

SKIP CODE:

Sampler Code

VARIABLE: SAMPNAME FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFRental TC

Testing Type

- 1 Black/White
- 2 Hispanic/White
- 3 Asian/White
- 4 Native American/White
- 5 Black/White Triad
- 6 Hispanic/White Triad
- 7 Asian/White Triad
- 8 Native American/White Triad

VARIABLE: TESTTYPE FORMAT: TEST TYPE: N

SKIP CODE:

Required Sequence

- 1 Minority-White
- 2 White-Minority
- 3 Minority - White - White
- 4 White - Minority - Minority

VARIABLE: SEQUENCE FORMAT: SEQUENCE TYPE: N

SKIP CODE:

Narrative Required

- 1 Yes
- 0 No

VARIABLE: NARRATIV FORMAT: YESNO TYPE: N

SKIP CODE:

Unit Type

- 1 Unfurnished
- 2 Furnished

VARIABLE: UNITYPE FORMAT: UNITYPR TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFRental TC

Source Type

- 1 Major Metropolitan Newspaper
- 2 Community Newspaper
- 3 Rental/Sales Guide
- 4 Internet

VARIABLE: SRCETYPE FORMAT: STYPE TYPE: N

SKIP CODE:

Date the Ad appeared (mm/dd/yy)

VARIABLE: ADDATE FORMAT: DATE TYPE: A

SKIP CODE:

Source Name

VARIABLE: SRCENAME FORMAT: SNAME TYPE: N

SKIP CODE:

Edition (if applicable)

VARIABLE: EDITION FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Location of Ad (Page, Column, Etc)

VARIABLE: GEOG FORMAT: \$ADTEXT TYPE: A

SKIP CODE:

Text of Ad

VARIABLE: ADTEXT FORMAT: \$BIGTXT TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFRental TC

Editor Name

VARIABLE: EDITNAME FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Release this test?

1 Yes

2 No

VARIABLE: RELEASE FORMAT: \$YESNO TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFSales TC

Transaction Type

R Rental

S Sales

VARIABLE: TRANTYPE FORMAT: \$TAFTYP TYPE: A

SKIP CODE:

Site

AG Augusta, GA

AH Anaheim, CA

BA Baltimore, MD

BU Buffalo, NY

CH Chicago, IL

CO Columbus, GA

DC Washington, DC

HN Honolulu, HI

HU Huntsville, AL

MB Mobile, AL

MI Miami, FL

MY Montgomery, AL

NS Nassau-Suffolk County, NY

NY New York, NY

OK Oakland, CA

PH Philadelphia, PA

PT Pittsburgh, PA

RO Rochester, NY

RV Riverside, CA

SD San Diego, CA

SF San Francisco, CA

SJ San Jose, CA

SV Savannah, GA

XX UI Internal Test Site

ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFSales TC

VARIABLE: WEEK FORMAT: INTEGR TYPE: N
SKIP CODE:

Ad Number

VARIABLE: AD_NO FORMAT: NO3 TYPE: N
SKIP CODE:

CONTROL

VARIABLE: CONTROL FORMAT: \$CONTROL TYPE: A
SKIP CODE:

Date of Issuance (mm/dd/yy)

VARIABLE: ISSUEDTE FORMAT: DATE TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFSales TC

Organization

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: ORGNAME FORMAT: \$SITE TYPE: A

SKIP CODE:

Sampler Code

VARIABLE: SAMPNAME FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFSales TC

Testing Type

- 1 Black/White
- 2 Hispanic/White
- 3 Asian/White
- 4 Native American/White
- 5 Black/White Triad
- 6 Hispanic/White Triad
- 7 Asian/White Triad
- 8 Native American/White Triad

VARIABLE: TESTTYPE FORMAT: TEST TYPE: N

SKIP CODE:

Required Sequence

- 1 Minority-White
- 2 White-Minority
- 3 Minority - White - White
- 4 White - Minority - Minority

VARIABLE: SEQUENCE FORMAT: SEQUENCE TYPE: N

SKIP CODE:

Narrative Required

- 1 Yes
- 0 No

VARIABLE: NARRATIV FORMAT: YESNO TYPE: N

SKIP CODE:

Unit Type

- 3 Single Family Home
- 4 Condo
- 5 Co-op
- 6 Mobile Home

VARIABLE: UNITYPE FORMAT: UNITYTYP TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFSales TC

Source Type

- 1 Major Metropolitan Newspaper
- 2 Community Newspaper
- 3 Rental/Sales Guide
- 4 Internet

VARIABLE: SRCETYPE FORMAT: STYPE TYPE: N

SKIP CODE:

Date the Ad appeared (mm/dd/yy)

VARIABLE: ADDATE FORMAT: DATE TYPE: A

SKIP CODE:

Source Name

VARIABLE: SRCENAME FORMAT: SNAME TYPE: N

SKIP CODE:

Edition (if applicable)

VARIABLE: EDITION FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Location of Ad (Page, Column, Etc)

VARIABLE: GEOG FORMAT: \$ADTEXT TYPE: A

SKIP CODE:

Text of Ad

VARIABLE: ADTEXT FORMAT: \$BIGTXT TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

TAFSales TC

Editor Name

VARIABLE: EDITNAME FORMAT: \$TEXT25 TYPE: A

SKIP CODE:

Release this test?

1 Yes

2 No

VARIABLE: RELEASE FORMAT: \$YESNO TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

Site

- AG Augusta, GA
- AH Anaheim, CA
- BA Baltimore, MD
- BU Buffalo, NY
- CH Chicago, IL
- CO Columbus, GA
- DC Washington, DC
- HN Honolulu, HI
- HU Huntsville, AL
- MB Mobile, AL
- MI Miami, FL
- MY Montgomery, AL
- NS Nassau-Suffolk County, NY
- NY New York, NY
- OK Oakland, CA
- PH Philadelphia, PA
- PT Pittsburgh, PA
- RO Rochester, NY
- RV Riverside, CA
- SD San Diego, CA
- SF San Francisco, CA
- SJ San Jose, CA
- SV Savannah, GA
- XX UI Internal Test Site
- ZZ UI Training Test Site

VARIABLE: SITECODE FORMAT: \$SITE TYPE: A

SKIP CODE:

TESTER ID#

VARIABLE: TESTERID FORMAT: TESTERID TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

CHARACTERISTICS OF TESTER APPLICANT

VARIABLE: header2 FORMAT: HEADER3 TYPE: H
SKIP CODE:

1.1 Applicant Name (firstname lastname)

VARIABLE: TNAME FORMAT: \$TEXT64 TYPE: A
SKIP CODE:

1.2 Street Address

VARIABLE: TADDR FORMAT: \$TEXT128 TYPE: A
SKIP CODE:

1.3 City

VARIABLE: TCITY FORMAT: \$TEXT32 TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.3 State

- AK AK - Alaska
- AL AL - Alabama
- AR AR - Arkansas
- AZ AZ - Arizona
- CA CA - California
- CO CO - Colorado
- CT CT - Connecticut
- DC DC - District of Columbia
- DE DE - Delaware
- FL FL - Florida
- GA GA - Georgia
- HI HI - Hawaii
- IA IA - Iowa
- ID ID - Idaho
- IL IL - Illinois
- IN IN - Indiana
- KS KS - Kansas
- KY KY - Kentucky
- LA LA - Louisiana
- MA MA - Massachusetts
- MD MD - Maryland
- ME ME - Maine
- MI MI - Michigan
- MN MN - Minnesota
- MO MO - Missouri
- MS MS - Mississippi
- MT MT - Montana
- NC NC - North Carolina
- ND ND - North Dakota
- NE NE - Nebraska
- NH NH - New Hampshire
- NJ NJ - New Jersey
- NM NM - New Mexico
- NV NV - Nevada
- NY NY - New York
- OH OH - Ohio
- OK OK - Oklahoma

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

- OR OR - Oregon
- PA PA - Pennsylvania
- RI RI - Rhode Island
- SC SC - South Carolina
- SD SD - South Dakota
- TN TN - Tennessee
- TX TX - Texas
- UT UT - Utah
- VA VA - Virginia
- VT VT - Vermont
- WA WA - Washington
- WI WI - Wisconsin
- WV WV - West Virginia
- WY WY - Wyoming

VARIABLE: TSTATE FORMAT: \$STATE TYPE: A
SKIP CODE:

1.3 Zip Code 00000

VARIABLE: TZIP FORMAT: \$ZIP TYPE: A
SKIP CODE:

1.4 Home Phone # (000)000-0000

VARIABLE: THPHONE FORMAT: PHONE TYPE: A
SKIP CODE:

1.4 Work Phone # (000)000-0000

VARIABLE: TWPHONE FORMAT: PHONE TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.5 Cell Phone # (000)000-0000

VARIABLE: TCPHONE FORMAT: PHONE TYPE: A

SKIP CODE:

1.5 Pager # (000)000-0000

VARIABLE: TPPHONE FORMAT: PHONE TYPE: A

SKIP CODE:

1.6 Fax Phone # (000)000-0000

VARIABLE: TFPHONE FORMAT: PHONE TYPE: A

SKIP CODE:

1.6 Email Address

VARIABLE: TEMAIL FORMAT: \$EMAIL TYPE: A

SKIP CODE:

1.7 Race

- 1 White
- 2 Black/African-American
- 3 American Indian/Native American
- 4 Asian/Pacific Islander
- 5 Other (Specify)

VARIABLE: APRACE FORMAT: APRACE TYPE: N

SKIP CODE:

1.7 Other [Specify]

VARIABLE: TRACESPY FORMAT: \$TEXT32 TYPE: A

SKIP CODE: txt_txt_txt('APRACE','TRACESPY','TNATORIG','5');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.8 National Origin

1 Non-Hispanic

2 Hispanic

VARIABLE: TNATORIG FORMAT: TNATORIG TYPE: N

SKIP CODE:

1.8a. If Hispanic, check appropriate categories

1 Mexican

2 Puerto Rican

3 Cuban

4 Dominican

5 Central American

6 South American

7 Other (Specify:)

VARIABLE: THISPNC FORMAT: THISPNC TYPE: N

SKIP CODE: slct_slct_txt('TNATORIG','THISPNC','THISPSPY','1');

1.8a Other [Specify]

VARIABLE: THISPSPY FORMAT: \$TEXT32 TYPE: A

SKIP CODE: txt_txt_txt('THISPNC','THISPSPY','TASIANG','7');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.8b If Asian/Pacific Islander, check appropriate categories

- 1 Chinese
- 2 Filipino
- 3 Japanese
- 4 Asian Indian
- 5 Korean
- 6 Vietnamese
- 7 Cambodian
- 8 Hmong
- 9 Laotian
- 10 Thai
- 11 Hawaiian
- 12 Samoan
- 13 Tongan
- 14 Guamanian
- 15 Other (Specify:)

VARIABLE: TASIANG FORMAT: TASIANG TYPE: N

SKIP CODE: txt_txt_txt('APRACE','TASIANG','TASIANS','4');

1.8b Other Asian/Pacific Islander [Specify]

VARIABLE: TASIANS FORMAT: \$TEXT32 TYPE: A

SKIP CODE: txt_txt_txt('TASIANG','TASIANS','TTRIBE','15');

1.8c If American Indian/Native American, which tribe(s)?

VARIABLE: TTRIBE FORMAT: \$TEXT32 TYPE: A

SKIP CODE: txt_txt_txt('APRACE','TTRIBE','TSEX','3');

1.9 Sex

- 0 Female
- 1 Male

VARIABLE: TSEX FORMAT: SEX TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)}. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.10 Date of Birth (mm/dd/yy)

VARIABLE: TDOB FORMAT: DATE TYPE: A

SKIP CODE:

1.11 Country of Origin

VARIABLE: TCOGIN FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.11 If not born in the U.S., how long have you lived in the U.S.?

- 1 Less than 1 year
- 2 1 to 5 years
- 3 6 to 10 years
- 4 11 to 20 years
- 5 over 20 years

VARIABLE: TTIMEUS FORMAT: TTIMEUS TYPE: N

SKIP CODE:

1.12 Do you live in the Metropolitan Area in which the testing is to be conducted?

- 1 Yes
- 0 No

VARIABLE: TMALIVE FORMAT: YESNO TYPE: N

SKIP CODE:

If Yes, how long have you lived in the area?

VARIABLE: header27 FORMAT: HEADER3 TYPE: H

SKIP CODE:

1.12 Months

VARIABLE: TLIVMON FORMAT: INTEGR TYPE: N

SKIP CODE: `chk_txt_txt('TMALIVE','TLIVMON','TLIVYR','1');`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.12 Years

VARIABLE: TLIVYR FORMAT: INTEGR TYPE: N

SKIP CODE: `chk_txt_chk('TMALIVE','TLIVYR','TPROFO','1');`

1.13 Are you proficient in any language other than English?

1 Yes

0 No

VARIABLE: TPROFO FORMAT: YESNO TYPE: N

SKIP CODE:

1.13 If YES, please specify

VARIABLE: TPROFOS FORMAT: \$TEXT32 TYPE: A

SKIP CODE: `chk_txt_txt('TPROFO','TPROFOS','TLANGHOM','1');`

1.13 Which language do you primarily speak at home?

VARIABLE: TLANGHOM FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.14 Are you currently Employed?

1 Yes

0 No

VARIABLE: TCUREMP FORMAT: YESNO TYPE: N

SKIP CODE:

If Yes, where are you employed? [includes self-employment]

VARIABLE: header34 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.14 Name of Employer

VARIABLE: TEMPLR FORMAT: \$TEXT64 TYPE: A
SKIP CODE: chk_txt_txt('TCUREMP','TEMPLR','TEADDR1','1');

1.14 Address of Employer

VARIABLE: TEADDR1 FORMAT: \$TEXT64 TYPE: A
SKIP CODE: chk_txt_txt('TCUREMP','TEADDR1','TEADDR2','1');

1.14 City, State Zip Code

VARIABLE: TEADDR2 FORMAT: \$TEXT64 TYPE: A
SKIP CODE: chk_txt_txt('TCUREMP','TEADDR2','TEMPLNGT','1');

1.14 Length of Employment

VARIABLE: TEMPLNGT FORMAT: \$TEXT64 TYPE: A
SKIP CODE: chk_txt_txt('TCUREMP','TEMPLNGT','TJOBITL','1');

1.14 Job Title

VARIABLE: TJOBITL FORMAT: \$TEXT64 TYPE: A
SKIP CODE: chk_txt_txt('TCUREMP','TJOBITL','TSUPERV','1');

14a Name of Supervisor

VARIABLE: TSUPERV FORMAT: \$TEXT32 TYPE: A
SKIP CODE: chk_txt_txt('TCUREMP','TSUPERV','TSUPPH','1');

14a Phone # (000)000-0000

VARIABLE: TSUPPH FORMAT: PHONE TYPE: A
SKIP CODE: chk_txt_txt('TCUREMP','TSUPPH','TPREVE','1');

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.15 Previous Types of Employment

VARIABLE: TPREVE FORMAT: TLONG TYPE: A

SKIP CODE: //chk_txt_chk('TCUREMP','TPREVE','TSTUDNT','1');

1.16 Are you currently a Student?

1 Yes

0 No

VARIABLE: TSTUDNT FORMAT: YESNO TYPE: N

SKIP CODE:

1.16 If Yes, where are you enrolled?

VARIABLE: TSTUDNSE FORMAT: \$TEXT32 TYPE: A

SKIP CODE: chk_txt_txt('TSTUDNT','TSTUDNSE','TSTUDNSC','1');

1.16 If Yes, what is your major course of study?

VARIABLE: TSTUDNSC FORMAT: \$TEXT64 TYPE: A

SKIP CODE: chk_txt_txt('TSTUDNT','TSTUDNSC','THIGHEDU','1');

1.17 Highest Level of Education Completed

1 Grade school or less

2 Some high school

3 GED

4 High School diploma

5 Some Vocational/Technical or business school

6 Vocational/technical/business certificate/diploma

7 Some college

8 Associates Degree (AA; AS)

9 Bachelor's Degree (BA; BS)

10 Some Graduate/ Professional School

11 Graduate/professional degree

VARIABLE: THIGHEDU FORMAT: TEDU TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.17 Graduate/professional Degree (Specify Degree)

VARIABLE: TDEGREE FORMAT: \$TEXT32 TYPE: A

SKIP CODE: txt_txt_txt('THIGHEDU','TDEGREE','TPEGAI','11')

1.18 Your Estimated Gross Annual Income

- 1 Under \$10,000
- 2 \$10,000 - \$19,999
- 3 \$20,000 - \$29,999
- 4 \$30,000 - \$39,999
- 5 \$40,000 - \$49,999
- 6 \$50,000 - \$74,999
- 7 \$75,000 - \$99,999
- 8 \$100,000 or more

VARIABLE: TPEGAI FORMAT: TPEGAI TYPE: N

SKIP CODE:

1.19 Your Household's Estimated Gross Annual Income

- 1 Under \$10,000
- 2 \$10,000 - \$19,999
- 3 \$20,000 - \$29,999
- 4 \$30,000 - \$39,999
- 5 \$40,000 - \$49,999
- 6 \$50,000 - \$59,999
- 7 \$60,000 - \$69,999
- 8 \$70,000 - \$79,999
- 9 \$80,000 - \$99,999
- 10 \$100,000 - \$149,999
- 11 \$150,000 or more

VARIABLE: THHEGAI FORMAT: THHEGAI TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

Household Information

VARIABLE: header50 FORMAT: HEADER2 TYPE: H

SKIP CODE:

Person

VARIABLE: TABHEAD1 FORMAT: THEADER TYPE: H

SKIP CODE:

Names of Others in Household

VARIABLE: TABHEAD2 FORMAT: THEADER TYPE: H

SKIP CODE:

Race

VARIABLE: TABHEAD3 FORMAT: THEADER TYPE: H

SKIP CODE:

Gender

VARIABLE: TABHEAD4 FORMAT: THEADER TYPE: H

SKIP CODE:

Date of Birth mm/dd/yy

VARIABLE: TABHEAD5 FORMAT: THEADER TYPE: H

SKIP CODE:

Relationship To Applicant

VARIABLE: TABHEAD6 FORMAT: THEADER TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

Occupation

VARIABLE: TABHEAD7 FORMAT: THEADER TYPE: H

SKIP CODE:

1.20 Person1

VARIABLE: THNM1 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.20

- 1 White
- 2 Black/African-American
- 3 American Indian/Native American
- 4 Asian/Pacific Islander
- 5 Other (Specify)

VARIABLE: THHRAC1 FORMAT: HHAPRACE TYPE: A

SKIP CODE:

1.20

- 0 Female
- 1 Male

VARIABLE: THHSEX1 FORMAT: SEX TYPE: N

SKIP CODE:

1.20 Date (mm/dd/yy)

VARIABLE: THHDOB1 FORMAT: DATE TYPE: A

SKIP CODE:

1.20

VARIABLE: THHREL1 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.20

VARIABLE: THHOCC1 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.20 Person2

VARIABLE: THHM2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.20

- 1 White
- 2 Black/African-American
- 3 American Indian/Native American
- 4 Asian/Pacific Islander
- 5 Other (Specify)

VARIABLE: THHRAC2 FORMAT: HHAPRACE TYPE: A

SKIP CODE:

1.20

- 0 Female
- 1 Male

VARIABLE: THHSEX2 FORMAT: SEX TYPE: N

SKIP CODE:

1.20 Date (mm/dd/yy)

VARIABLE: THHDOB2 FORMAT: DATE TYPE: A

SKIP CODE:

1.20

VARIABLE: THHREL2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.20

VARIABLE: THHOCC2 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.20 Person3

VARIABLE: THHM3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.20

- 1 White
- 2 Black/African-American
- 3 American Indian/Native American
- 4 Asian/Pacific Islander
- 5 Other (Specify)

VARIABLE: THHRAC3 FORMAT: HHAPRACE TYPE: A

SKIP CODE:

1.20

- 0 Female
- 1 Male

VARIABLE: THHSEX3 FORMAT: SEX TYPE: N

SKIP CODE:

1.20 Date (mm/dd/yy)

VARIABLE: THHDOB3 FORMAT: DATE TYPE: A

SKIP CODE:

1.20

VARIABLE: THHREL3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.20

VARIABLE: THHOCC3 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.20 Person4

VARIABLE: THHM4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.20

- 1 White
- 2 Black/African-American
- 3 American Indian/Native American
- 4 Asian/Pacific Islander
- 5 Other (Specify)

VARIABLE: THHRAC4 FORMAT: HHAPRACE TYPE: A

SKIP CODE:

1.20

- 0 Female
- 1 Male

VARIABLE: THHSEX4 FORMAT: SEX TYPE: N

SKIP CODE:

1.20 Date (mm/dd/yy)

VARIABLE: THHDOB4 FORMAT: DATE TYPE: A

SKIP CODE:

1.20

VARIABLE: THHREL4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.20

VARIABLE: THHOCC4 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.20 Person5

VARIABLE: THHM5 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.20

- 1 White
- 2 Black/African-American
- 3 American Indian/Native American
- 4 Asian/Pacific Islander
- 5 Other (Specify)

VARIABLE: THHRAC5 FORMAT: HHAPRACE TYPE: A

SKIP CODE:

1.20

- 0 Female
- 1 Male

VARIABLE: THHSEX5 FORMAT: SEX TYPE: N

SKIP CODE:

1.20 Date (mm/dd/yy)

VARIABLE: THHDOB5 FORMAT: DATE TYPE: A

SKIP CODE:

1.20

VARIABLE: THHREL5 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

1.20

VARIABLE: THHOCC5 FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

1.21 Have you ever pled guilty to or been convicted of a crime (other than juvenile or traffic offence) within the last ten years?

1 Yes

0 No

VARIABLE: TCRIME FORMAT: YESNO TYPE: N

SKIP CODE:

1.21 If YES, please describe

VARIABLE: TCRIMES FORMAT: \$TEXT128 TYPE: A

SKIP CODE: `chk_txt_chk('TCRIME','TCRIMES','TFRAUD','1');`

1.21 Have you ever pled guilty to or been convicted of a crime related to fraud or perjury?

1 Yes

0 No

VARIABLE: TFRAUD FORMAT: YESNO TYPE: N

SKIP CODE:

1.22 If Yes, please describe

VARIABLE: TFRAUDS FORMAT: \$TEXT128 TYPE: A

SKIP CODE: `chk_txt_txt('TFRAUD','TFRAUDS','TTIMECUR','1');`

APPLICANT EXPERIENCE AS A HOMESEAKER

VARIABLE: header85 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

2.1 Length of Time at Current Residence

- 1 Less than 1 year
- 2 1 to 2 years
- 3 3 to 5 years
- 4 6 to 10 years
- 5 More than 10 years

VARIABLE: TTIMECUR FORMAT: TTIMECUR TYPE: N

SKIP CODE:

2.2 Do you presently rent or own your home?

- 1 rent
- 2 own
- 3 Other (Specify)

VARIABLE: TCURTENR FORMAT: TCURTENR TYPE: N

SKIP CODE:

2.2 Other [Specify]

VARIABLE: TCURTENS FORMAT: \$TEXT32 TYPE: A

SKIP CODE: txt_txt_txt('TCURTENR','TCURTENS','TDWLTYP','3')

2.3 Type of Dwelling

- 1 Single family home
- 2 Mobile home
- 3 Apartment
- 4 Condominium
- 5 Co-op
- 6 Duplex
- 7 Other (Specify)

VARIABLE: TDWLTYP FORMAT: HOMTYP TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

2.3 Other [Specify]

VARIABLE: TDWLTYP5 FORMAT: \$TEXT32 TYPE: A

SKIP CODE: txt_txt_txt('TDWLTYP','TDWLTYP5','TMORTFIN','7')

2.4 How many times have you purchased a home using some type of mortgage financing?

- 1 Never
- 2 Once
- 3 Two or Three times
- 4 More than three times

VARIABLE: TMORTFIN FORMAT: TMORTFIN TYPE: N

SKIP CODE:

2.5 Are you looking to rent or purchase housing at the present time?

- 1 Yes
- 0 No

VARIABLE: THOMEHNT FORMAT: YESNO TYPE: N

SKIP CODE:

2.5 If Yes, please describe the type of housing you are seeking

VARIABLE: THMHNTS FORMAT: \$TEXT128 TYPE: A

SKIP CODE: chk_txt_chk('THOMEHNT','THMHNTS','TEXPERNC','1');

APPLICANT EXPERIENCE AS A TESTER

VARIABLE: header94 FORMAT: HEADER3 TYPE: H

SKIP CODE:

3.1 Have you ever been a tester?

- 1 Yes
- 0 No

VARIABLE: TEXPERNC FORMAT: YESNO TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

3.2 If Yes, please estimate how many tests you have done

VARIABLE: TNOTESTS FORMAT: NSHORT TYPE: N

SKIP CODE: `chk_txt_chk('TEXPERNC','TNOTESTS','TTESTTP1','1');`

If Yes, what type(s) of testing have you conducted in the past?

VARIABLE: header97 FORMAT: HEADER3 TYPE: H

SKIP CODE:

3.2a Rental

1 Yes

0 No

VARIABLE: TTESTTP1 FORMAT: YESNO TYPE: N

SKIP CODE: `chk_chk_chk('TEXPERNC','TTESTTP1','TTESTTP2','1');`

3.2a Sales

1 Yes

0 No

VARIABLE: TTESTTP2 FORMAT: YESNO TYPE: N

SKIP CODE: `chk_chk_chk('TEXPERNC','TTESTTP2','TTESTTP3','1');`

3.2a Lending

1 Yes

0 No

VARIABLE: TTESTTP3 FORMAT: YESNO TYPE: N

SKIP CODE: `chk_chk_chk('TEXPERNC','TTESTTP3','TTESTTP4','1');`

3.2a Insurance

1 Yes

0 No

VARIABLE: TTESTTP4 FORMAT: YESNO TYPE: N

SKIP CODE: `chk_chk_chk('TEXPERNC','TTESTTP4','TTESTTP5','1');`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

3.2a Employment

1 Yes

0 No

VARIABLE: TTESTTP5 FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('TEXPERNC','TTESTTP5','TTESTTP6','1');

3.2a Public Accommodations

1 Yes

0 No

VARIABLE: TTESTTP6 FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_chk('TEXPERNC','TTESTTP6','TTESTTP7','1');

3.2a Other

1 Yes

0 No

VARIABLE: TTESTTP7 FORMAT: YESNO TYPE: N

SKIP CODE: chk_chk_txt('TEXPERNC','TTESTTP7','TTSTTYP5','1');

3.2a [Specify]

VARIABLE: TTSTTYP5 FORMAT: \$TEXT64 TYPE: A

SKIP CODE: chk_txt_chk('TTESTTP7','TTSTTYP5','TSM','1');

AVAILABILITY TO TEST

VARIABLE: header10 FORMAT: HEADER3 TYPE: H

SKIP CODE:

Time

VARIABLE: COLTHD01 FORMAT: THEADER TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

Sunday

VARIABLE: COLTHD02 FORMAT: THEADER TYPE: H

SKIP CODE:

Monday

VARIABLE: COLTHD03 FORMAT: THEADER TYPE: H

SKIP CODE:

Tuesday

VARIABLE: COLTHD04 FORMAT: THEADER TYPE: H

SKIP CODE:

Wednesday

VARIABLE: COLTHD05 FORMAT: THEADER TYPE: H

SKIP CODE:

Thursday

VARIABLE: COLTHD06 FORMAT: THEADER TYPE: H

SKIP CODE:

Friday

VARIABLE: COLTHD07 FORMAT: THEADER TYPE: H

SKIP CODE:

Saturday

VARIABLE: COLTHD08 FORMAT: THEADER TYPE: H

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

4.1 Morning (9:00 a.m. to 12 noon)

1 Yes

0 No

VARIABLE: TSM

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TMM

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TTM

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TWM

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TTHM

FORMAT: YESNO

TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

4.1

1 Yes

0 No

VARIABLE: TFM

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TSAM

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1 **Afternoon
(12 noon to
5:00 p.m.)**

1 Yes

0 No

VARIABLE: TSA

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TMA

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TTA

FORMAT: YESNO

TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

4.1

1 Yes

0 No

VARIABLE: TWA

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TTHA

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TFA

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TSAA

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1 Evening
(5:00 p.m. to 9:00 p.m.)

1 Yes

0 No

VARIABLE: TSE

FORMAT: YESNO

TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

4.1

1 Yes

0 No

VARIABLE: TME

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TTE

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TWE

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: THE

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.1

1 Yes

0 No

VARIABLE: TFE

FORMAT: YESNO

TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

4.1

1 Yes

0 No

VARIABLE: TSAE

FORMAT: YESNO

TYPE: N

SKIP CODE:

4.2 Do you have a valid driver's license?

1 Yes

0 No

VARIABLE: TDRIVER

FORMAT: YESNO

TYPE: N

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

4.2a If Yes, what state issued your current driver's license?

- AK AK - Alaska
- AL AL - Alabama
- AR AR - Arkansas
- AZ AZ - Arizona
- CA CA - California
- CO CO - Colorado
- CT CT - Connecticut
- DC DC - District of Columbia
- DE DE - Delaware
- FL FL - Florida
- GA GA - Georgia
- HI HI - Hawaii
- IA IA - Iowa
- ID ID - Idaho
- IL IL - Illinois
- IN IN - Indiana
- KS KS - Kansas
- KY KY - Kentucky
- LA LA - Louisiana
- MA MA - Massachusetts
- MD MD - Maryland
- ME ME - Maine
- MI MI - Michigan
- MN MN - Minnesota
- MO MO - Missouri
- MS MS - Mississippi
- MT MT - Montana
- NC NC - North Carolina
- ND ND - North Dakota
- NE NE - Nebraska
- NH NH - New Hampshire
- NJ NJ - New Jersey
- NM NM - New Mexico
- NV NV - Nevada
- NY NY - New York
- OH OH - Ohio
- OK OK - Oklahoma

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

- OR OR - Oregon
- PA PA - Pennsylvania
- RI RI - Rhode Island
- SC SC - South Carolina
- SD SD - South Dakota
- TN TN - Tennessee
- TX TX - Texas
- UT UT - Utah
- VA VA - Virginia
- VT VT - Vermont
- WA WA - Washington
- WI WI - Wisconsin
- WV WV - West Virginia
- WY WY - Wyoming

VARIABLE: TDRIVERS FORMAT: \$STATE TYPE: A

SKIP CODE: `chk_txt_chk('TDRIVER','TDRIVERS','TOWNCAR','1');`

4.3 Do you own or have regular access to a car that you can use for testing?

- 1 Yes
- 0 No

VARIABLE: TOWNCAR FORMAT: YESNO TYPE: N

SKIP CODE:

4.4 Do you have any prior experience using a computer (e.g. word processing, data entry, Internet, etc)?

- 1 Yes
- 0 No

VARIABLE: TCOMPUTE FORMAT: YESNO TYPE: N

SKIP CODE:

4.4 If Yes, please describe experience

VARIABLE: TCOMPUTS FORMAT: \$TEXT128 TYPE: A

SKIP CODE: `chk_txt_txt('TCOMPUTE','TCOMPUTS','TDATESIG','1');`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

This form is complete

1 Yes

0 No

VARIABLE: COMP FORMAT: YESNO TYPE: N

SKIP CODE:

5.1 Date (mm/dd/yy)

VARIABLE: TDATESIG FORMAT: DATE TYPE: A

SKIP CODE:

FOR OFFICE USE ONLY

VARIABLE: header13 FORMAT: HEADER3 TYPE: H

SKIP CODE:

6.3 Is this Applicant Proficient in English Language and Writing?

1 Yes

0 No

VARIABLE: TENGLISH FORMAT: YESNO TYPE: N

SKIP CODE:

6.4 Does the Applicant have a Discernible Accent of Any Kind?

1 Yes

0 No

VARIABLE: TACCENT FORMAT: YESNO TYPE: N

SKIP CODE:

6.4a If Yes, Please Describe

VARIABLE: TACCNTS FORMAT: \$TEXT32 TYPE: A

SKIP CODE: `chk_txt_chk('TACCENT','TACCNTS','TVISRACE','1');`

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

6.5 Is this Applicant's Race or Ethnicity Clearly Discernible?

1 Yes

0 No

VARIABLE: TVISRACE FORMAT: YESNO TYPE: N

SKIP CODE:

6.2 Was the applicant selected?

1 Yes

0 No

VARIABLE: TAPPEL FORMAT: YESNO TYPE: N

SKIP CODE:

6.2b If No, Why Not?

VARIABLE: TAPNOTS FORMAT: \$TEXT128 TYPE: A

SKIP CODE: `chk_txt_chk('TAPPEL','TAPNOTS','TENGLISH','0');`

FOR SELECTED TESTERS ONLY

VARIABLE: header14 FORMAT: HEADER3 TYPE: H

SKIP CODE:

6.6 Tester Attended Training Session Held On (mm/dd/yy)

VARIABLE: TTRNDATE FORMAT: DATE TYPE: A

SKIP CODE:

6.6 Name/Location of Facility

VARIABLE: TTRNF FORMAT: \$TEXT32 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value). The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

6.6 City/State

VARIABLE: TTRNST FORMAT: \$TEXT64 TYPE: A
SKIP CODE:

6.7 Tester Completed a Practice Test on (mm/dd/yy)

VARIABLE: TPRTST FORMAT: DATE TYPE: A
SKIP CODE:

6.8 Tester Entered Practice Test Data on (mm/dd/yy)

VARIABLE: TPRENT FORMAT: DATE TYPE: A
SKIP CODE:

6.11 Tester Name to be used for Testing (firstname lastname)

VARIABLE: TFNAME FORMAT: \$TEXT64 TYPE: A
SKIP CODE:

6.1 Tester Address to be used for Testing

VARIABLE: TFADHD1 FORMAT: HEADER3 TYPE: H
SKIP CODE:

6.10 First line of address

VARIABLE: TFADD1 FORMAT: \$TEXT64 TYPE: A
SKIP CODE:

6.10 Second line of address (city/state/zip)

VARIABLE: TFADD2 FORMAT: \$TEXT64 TYPE: A
SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.

Tester App

6.12 Voice Mail Number Assigned to Tester (000)000-0000

VARIABLE: TVPHONE FORMAT: PHONE TYPE: A

SKIP CODE:

6.9 COMMENTS

VARIABLE: TCOMMEN FORMAT: \$TEXT128 TYPE: A

SKIP CODE:

Skip code syntax (javascript) is: function(var checked, var skipped, go to var, skip value)]. The functions blur(), and lock() disable data entry. Most functions skip if checked variable=skip value, but there are a few functions where skip patterns are handled differently.